

PRODUCT GUIDE



DESIGNED IN USA
DRIVEN WORLDWIDE



ARROYO
TIRES



Arroyo Tire is an innovative brand made with the highest technology to bring you the best quality at the most affordable price. These tires offer superior performance, precision, handling, braking grip, comfort and durability, along with low noise level. Arroyo tire is dedicated to delivering improved savings and operational efficiencies, while reducing environmental impact. These tires are built with your needs and safety in mind and ready to adapt when those needs change.



CONTENTS

Passenger Tires

	Arroyo Grand Sport A/S	page 4
	Arroyo Grand Sport 2	page 10
NEW	Arroyo Grand Sport Plus	page 14
	Arroyo Eco Pro A/S	page 20
NEW	Arroyo Eco Pro A/S Plus	page 22
NEW	Arroyo Run Flat Arroyo Run Flat +	page 24-25
	Arroyo Ultra Sport A/S	page 38
NEW	Arroyo Razzo Sport A/S	page 42

Light Truck / SUV Tires

	Arroyo Eco Pro H/T	page 26
NEW	Arroyo Corso UHT	page 30
NEW	Arroyo Eco Pro H/T Plus	page 32
	Arroyo Eco Pro H/T 2	page 34
	Arroyo Van Pro 2 / Van Pro 3	page 46 - 47
NEW	Arroyo Van Pro Plus / Van Pro	page 48 - 49
	Arroyo Tamarock A/T	page 52
	Arroyo Tamarock M/T	page 58
NEW	Arroyo Tamarock R/T	page 62
NEW	Arroyo Tamarock X R/T	page 68

NEW	Arroyo ST SEMI-STEEL / ALL-STEEL	page 70 - 71
------------	----------------------------------	--------------

NEW Commercial (TBR) Tires

	STEER/ALL-POSITION - SMART WAY	
	Arroyo AR 1000 - AR 1100	page 74
	REGIONAL CLOSED-SHOULDER DRIVE - SMART WAY	
	Arroyo AR 2000 - AR 2200	page 76
	REGIONAL OPEN-SHOULDER DRIVE	
	Arroyo AR 3000	page 78
	TRAILER	
	Arroyo AR 4000	page 80
	ON-OFF ROAD / MIXED-SERVICE	
	Arroyo AR 5000	page 82
	REGIONAL PICK-UP/DELIVERY	
	Arroyo AR 6000	page 84



LIMITED TIRE WARRANTY PLAN

Arroyo Tire Limited Warranty Plan	page 86
-----------------------------------	---------



UHP All-Season
Ultra High Performance

GRAND SPORT A/S



- Sizes - 14, 15, 16, 17, 18, 19, 20 & 22" Rim Diameter 25, 30, 35, 40, 45, 50, 55 & 60 Series Aspect Ratio
- 500 U.T.Q.G.
- 10/32 Tread Depth
- Jointless Nylon Band Spiral wound for uniformity
Increases strength in the high stress shoulder area.
- 2 Wide Steel Belts
Strengthen the overall tread area.
Provides stability, excellent wear character & long mileage.



SIZES
COMING
SOON

Wheel Dia.	TIRE SIZE
23"	285/40R23
	325/35R23

GRAND SPORT A/S

Wheel Dia.	TIRE SIZE	LOAD AND SPEED INDEX	EUROPEAN STANDARD RIM	AMERICAN STANDARD RIM	REC RIM WIDTH IN.	TREAD DEPTH MM	SECTION WIDTH MM	OVERALL DIAMETER MM	MAX LOAD KGS LBS	MAX INFLATION KPA PSI	UTQG	PLY RATING
14"	185/60R14	82H	5.0-5.5-6.5	5.0-5.5-6.5	5 1/2J	7.8	189	578	475 1047	300 44	500 A A	/
15"	185/55R15	82V	5.0-6.0-6.5	5.0-6.0-6.5	6J	7.8	194	585	475 1047	300 44	500 A A	/
	195/50R15	82V	5.5-6.0-7.0	5.5-6.0-7.0	6J	8	201	577	475 1047	300 44	500 A A	/
	195/55R15	85V	5.5-6.0-7.0	5.5-6.0-7.0	6J	8	201	595	515 1135	300 44	500 A A	/
16"	NEW 185/55R16	87V	5.0-6.0-6.5	5.0-6.0-6.5	6J	7.8	194	610	545 1201	340 49	500 A A	/
	195/50ZR16	84W	5.5-6-6.5	5.5-6-6.5	6	7.4	201	602	560 1102	300 44	500A A	4PR
	195/55ZR16	91W	5.5-6.0-7.0	5.5-6.0-7.0	6J	8	201	620	615 1356	340 49	500 A A	/
	205/45ZR16	87W	6.5-7.0-7.5	6.5-7.0-7.5	7J	8	206	590	545 1201	340 49	500 A A	/
	205/50ZR16	87W	5.5-6.5-7.5	5.5-6.5-7.5	6 1/2 J	8	214	612	545 1201	300 44	500 A A	/
	205/55ZR16	94W	5.5-6.5-7.5	5.5-6.5-7.5	6 1/2J	8	214	632	670 1477	340 49	500 A A	/
	205/55ZR16	94W	6-6.5-7	6-6.5-7	6.5	/	214	632	670 1477	340 49	500 A A	4PR
	215/55ZR16	97W	6.0-7.0-7.5	6.0-7.0-7.5	7 J	8	226	642	730 1609	340 49	500 A A	/
17"	225/55ZR16	95W	6.0-7.0-8.0	6.0-7.0-8.0	7J	8	233	654	690 1521	300 44	500 A A	/
	205/40ZR17	84W	7.0-7.5-8.0	/	7 1/2J	8	212	596	500 1102	340 49	500 A A	/
	205/45ZR17	88W	6.5-7.0-7.5	/	7J	8	206	616	560 1235	340 49	500 A A	/
	205/50ZR17	93W	5.5-6.5-7.5	5.5-6.5-7.5	6 1/2J	8	214	638	650 1433	340 49	500 A A	/
	205/55R17	95V	5.0-6.5-7.5	/	6 1/2J	8	214	658	690 1521	340 49	500 A A	/
	215/45ZR17	91W	7.0-8.0	7.0-8.0	7J	8	213	626	615 1356	340 49	500 A A	/
	215/45ZR17	91W	6.5-7-7.5	6.5-7-7.5	7	/	213	626	615 1356	340 49	420 A A	4PR
	215/50ZR17	95W	6.0-7.0-7.5	6.0-7.0-7.5	7J	8	226	648	690 1521	340 49	500 A A	/
	215/55ZR17	98W	6.0-7.0-7.5	6.0-7.0-7.5	7J	8	226	668	750 1653	340 49	500 A A	/
	215/55ZR17	98W	6.5-7-7.5	6.5-7-7.5	7	/	226	668	750 1653	340 49	420 A A	4PR
	225/45ZR17	94Y	7.0-7.5-8.5	7.0-7.5-8.5	7 1/2J	8	225	634	670 1477	340 49	500 A A	/
	225/45ZR17	94Y	7-7.5-8	7-7.5-8	7.5	/	225	634	670 1477	340 49	500 A A	4PR
	225/50ZR17	98W	6.0-7.0-8.0	6.0-7.0-8.0	7J	8	233	658	750 1653	340 49	500 A A	/
	225/55ZR17	101W	6.0-7.0-8.0	6.0-7.0-8.0	7J	8	233	680	825 1819	340 49	500 A A	/
	235/45ZR17	97W	7.5-8.0-9.0	7.5-8.0-9.0	8J	8	236	644	730 1609	340 49	500 A A	/
	235/50ZR17	100W	7.0-7.5-8.5	6.5-7.5-8.5	7 1/2J	8	245	668	800 1764	340 49	500 A A	/
18"	235/55ZR17	103W	6.5-7.5-8.5	6.5-7.5-8.5	7 1/2J	8.3	245	690	875 1929	340 49	500 A A	/
	235/60R17	102H	6.5-7.0-8.5	6.5-7.0-8.5	7J	8	240	714	850 1874	300 44	500 A A	/
	245/40ZR17	95W	8.0-8.5-9.5	8.0-8.5-9.5	8 1/2J	8	248	628	690 1521	340 49	500 A A	/
	245/45ZR17	99W	7.5-8.0-9.0	7.5-8.0-9.0	8J	8	243	652	775 1709	340 49	500 A A	/
	NEW 215/35ZR18	84W	7-7.5-8	7-7.5-8	7.5	7.4	218	607	500 1102	340 49	500 A A	4PR
	215/40ZR18	89W	7.0-7.5-8.5	7.0-7.5-8.5	7 1/2 J	8	218	629	580 1279	340 49	500 A A	/
	215/45ZR18	89W	7.0-8.0	7.0-8.0	7J	8	213	651	580 1279	300 44	500 A A	/
	NEW 215/50R18	92V			7.5	10	217	673	630 1389	300 44	600AA	4PR
	215/55R18	95V	6.0-7.0-7.5	6.0-7.0-7.5	7J	8	226	693	690 1521	300 44	500 A A	/
	225/40ZR18	92W	7.5-8.0-9.0	7.5-8.0-9.0	8J	8	230	637	630 1389	340 49	500 A A	/
19"	225/45ZR18	95W	7.0-7.5-8.5	7.0-7.5-8.5	7 1/2J	8	225	659	690 1521	340 49	500 A A	/
	225/50ZR18	99W	6.0-7.0-8.0	6.0-7.0-8.0	7J	8	233	683	775 1709	340 49	500 A A	/
	225/55R18	102V	6.0-7.0-8.0	6.0-7.0-8.0	7J	8	233	705	1030 2271	340 49	500 A A	/



UHP All-Season
Ultra High Performance

GRAND SPORT A/S



PATTERN INTRODUCTIONS

OUTSIDE INSIDE




1. 4 wide longitudinal grooves provide good water evacuation for excellent handling performance on wet roads.



2. Outside Anti Eccentric wear block design
Anti eccentric wear blocks on outer shoulder can increase the tread contact area at braking to obtain uniform contact pressure, which can avoid eccentric wear.



3. Partial Slanted Grooves interrupt air flow across the tread to decrease noise. Partial slanted grooves also can provide stability during cornering



4. Wide Grooves and fine sipes cut through water film to provide wet traction, and greatly reduce noise , providing a comfortable driving experience.



5. Silent pitch variation and sequence design Optimization of pitch width and sequence effectively reduce the noise resonance, resulting in a quieter ride.

GRAND SPORT A/S

Wheel Dia.	TIRE SIZE	LOAD AND SPEED INDEX	EUROPEAN STANDARD RIM	AMERICAN STANDARD RIM	REC RIM WIDTH IN.	TREAD DEPTH MM	SECTION WIDTH MM	OVERALL DIAMETER MM	MAX LOAD KGS LBS	MAX INFLATION KPA PSI	UTQG	PLY RATING
18"	235/40ZR18	95W	8.0-8.5-9.5	8.0-8.5-9.5	8 1/2J	8	241	645	690 1521	340 49	500 A A	/
	235/45ZR18	98W	7.5-8.0-9.0	7.5-8.0-9.0	8J	8	236	669	750 1653	340 49	500 A A	/
	235/45ZR18	98W	7.5-8-8.5	7.5-8-8.5	8		236	669	750 1653	340 49	500 A A	4PR
	235/50ZR18	101W	6.5-7.5-8.5	6.5-7.5-8.5	7 1/2J	8	245	693	825 1819	340 49	500 A A	/
	245/40ZR18	97W	8.0-8.5-9.5	8.0-8.5-9.5	8 1/2J	8	248	653	730 1609	340 49	500 A A	/
	245/45ZR18	100W/Y	7.5-8.0-9.0	7.5-8.0-9.0	8J	8	243	677	800 1764	340 49	500 A A	/
	245/50ZR18	100W	7.0-7.5-8.5	7.0-7.5-8.5	7 1/2J	8	253	703	800 1764	300 44	500 A A	/
	245/55ZR18	103W	7.0-7.5-8.5	7.0-7.5-8.5	7 1/2J	8	253	727	875 1929	300 44	500 A A	/
	255/35ZR18	94W	8.5-9.0-10.0	8.5-9.0-10.0	9 J	8	260	635	670 1477	340 49	500 A A	/
	255/40ZR18	99W	8.5-9.0-10.0	8.5-9.0-10.0	9J	8	260	661	775 1709	340 49	500 A A	/
	255/55ZR18	109W	7.0-8.0-9.0	7.0-8.0-9.0	8J	8	265	737	1030 2271	340 49	500 A A	/
	NEW 255/60R18	112V	7-7.5-8	7-7.5-8	7.5	7.6	260	763	1120 2469	340 49	500 A A	4PR
	265/35ZR18	97W	9.0-9.5-10.5	9.0-9.5-10.5	9 1/2 J	8	271	643	730 1609	340 49	500 A A	/
	NEW 275/40ZR18	99Y	9-9.5-10	9-9.5-10	9.5	7.6	278	677	775 1709	300 44	500 A A	4PR
19"	225/40ZR19	93W	7.5-8.0-9.0	/	8J	8	230	663	650 1433	340 49	500 A A	/
	225/45ZR19	96W	7.0-7.5-8.5	7.0-7.5-8.5	7 1/2 J	8	225	685	710 1565	340 49	500 A A	/
	225/55R19	103XL/V	6.0-7.0-8.0	6.0-7.0-8.0	7J	8	233	731	875 1929	340 50	500 A A	/
	235/35ZR19	91W	8.0-8.5-9.5	/	8 1/2J	8	241	647	615 1356	340 49	500 A A	/
	235/40ZR19	96W	8.0-8.5-9.5	8.0-8.5-9.5	8 1/2J	8	241	671	710 1565	340 49	500 A A	/
	235/40ZR19	96W	8-8.5-9	8-8.5-9	8.5		241	671	710 1565	340 49	500AA	4PR
	235/45ZR19	99W	7.5-8.0-9.0	7.5-8.0-9.0	8J	8	236	695	775 1709	340 49	500 A A	/
	235/50ZR19	103W	6.5-7.5-8.5	6.5-7.5-8.5	7 1/2J	8	245	719	875 1929	340 49	500 A A	/
	235/55R19	105V	6.5-7.5-8.5	6.5-7.5-8.5	7 1/2J	8	245	741	925 2039	340 49	500 A A	/
	235/55R19	105V	7-7.5-8	7-7.5-8	7.5		245	741	925 2039	340 49	500 A A	4PR
	NEW 235/65R19	109V	6.5-7-7.5	6.5-7-7.5	7	7.6	240	789	1030 2271	340 49	500 A A	4PR
	245/35ZR19	97W	8.0-8.5-9.5	8.0-8.5-9.5	8 1/2J	8	248	655	730 1609	340 49	500 A A	/
	245/40ZR19	98W/Y	8.0-8.5-9.5	8.0-8.5-9.5	8 1/2J	8	248	679	750 1653	340 49	500 A A	/
	245/45ZR19	102W	7.5-8.0-9.0	7.5-8.0-9.0	8 J	8	243	703	850 1874	340 49	500 A A	/
	245/50ZR19	105XL/W	/	7.0-7.5-8.5	7 1/2J	8	253	729	925 2039	340 50	500 A A	/
	245/55ZR19	103W	7.0-7.5-8.5	7.0-7.5-8.5	7 1/2J	8	253	753	875 1929	300 44	500 A A	/
	255/35ZR19	96W	8.5-9.0-10.0	/	9J	8	260	661	710 1565	340 49	500 A A	/
	255/40ZR19	100W	8.5-9.0-10.0	8.5-9.0-10.0	9J	8	260	687	800 1764	340 49	500 A A	/
	255/45ZR19	104W	8.0-8.5-9.5	8.0-8.5-9.5	8 1/2J	8	255	713	900 1984	340 49	500 A A	/
	255/55ZR19	111W	7.0-8.0-9.0	/	8J	8	265	763	1090 2403	340 49	500 A A	/
	265/30ZR19	93W	9.0-9.5-10.0	/	9 1/2J	8	271	643	650 1433	340 49	500 A A	/
	265/35ZR19	98XL/Y	9.0-9.5-10.5	/	9 1/2J	8	271	669	750 1653	340 50	500 A A	/
	265/50ZR19	110XL/W	7.5-8.5-9.5	/	8 1/2J	8	277	749	1060 2337	340 49	500 A A	/
	275/30ZR19	96W	9.0-9.5-10.0	9.0-9.5-10.0	9 1/2J	8	278	649	710 1565	340 49	500 A A	/
	275/35ZR19	100W	9.0-9.5-11.0	/	9 1/2J	8	278	675	800 1764	340 49	500 A A	/
	275/40ZR19	101Y	9.0-9.5-11.0	9.0-9.5-11.0	9 1/2J	8	278	703	825 1819	300 44	500 A A	/



GRAND SPORT A/S

Wheel Dia.	TIRE SIZE	LOAD AND SPEED INDEX	EUROPEAN STANDARD RIM	AMERICAN STANDARD RIM	REC RIM WIDTH IN.	TREAD DEPTH MM	SECTION WIDTH MM	OVERALL DIAMETER MM	MAX LOAD KGS LBS	MAX INFLATION KPA PSI	UTQG	PLY RATING
19"	NEW 275/45ZR19	108W	8.5-9-9.5	8.5-9-9.5	9	7.6	273	731	1000 2205	340 49	500 A A	4PR
	275/55R19	111V	7.5-8.5-9.5	/	8 1/2J	8.3	284	785	1090 2403	300 44	500 A A	/
20"	225/35ZR20	93W	7.5-8.0-9.0	7.5-8.0-9.0	8J	8	230	666	650 1433	340 49	500 A A	/
	235/35ZR20	92XL/Y	8.0-8.5-9.5	/	8 1/2J	8	241	672	630 1389	340 50	500 A A	/
	235/45ZR20	100XL/W	7.5-8.0-9.0	7.5-8.0-9.0	8J	8	236	720	800 1764	340 50	500 A A	/
	235/50ZR20	104XL/W	6.5-7.5-8.5	/	7 1/2J	8	245	744	900 1984	340 50	500 A A	/
	235/55ZR20	102W	6.5-7.5-8.5	6.5-7.5-8.5	7 1/2J	8	245	766	850 1874	300 44	500 A A	/
	235/55ZR20	102W	7-7.5-8	7-7.5-8	7.5		245	766	850 1874	300 44	500 A A	4PR
	245/35ZR20	95W	8.0-8.5-9.5	/	8 1/2J	8	248	680	690 1521	340 49	500 A A	/
	245/40ZR20	99W/Y	8.0-8.5-9.5	8.0-8.5-9.5	8 1/2J	8	248	704	775 1709	340 49	500 A A	/
	245/45ZR20	103W	7.5-8.0-9.0	7.5-8.0-9.0	8J	8	243	728	875 1929	340 49	500 A A	/
	245/45ZR20	103W	7.5-8-8.5	7.5-8-8.5	8		243	728	875 1929	340 49	500 A A	4PR
	255/35ZR20	97W	8.5-9.0-10.0	8.5-9.0-10.0	9 J	8	260	686	730 1609	340 49	500 A A	/
	NEW 255/40ZR20	101W	8.5-9-9.5	8.5-9-9.5	9	7.6	260	712	825 1819	340 49	500 A A	4PR
	255/45R20	105W	8.0-8.5-9.5	8.0-8.5-9.5	8 1/2J	8	255	738	925 2039	340 49	500 A A	/
	255/50ZR20	109V	7.0-8.0-8.5	7.0-8.0-9.0	8 J	8	265	764	1030 2271	340 49	500 A A	/
	255/55R20	110H	7.0-8.0-9.0	7.0-8.0-9.0	8J	8	265	788	1060 2337	340 49	500 A A	/
	NEW 255/60R20	113Y	/	/	9	6.6	257	741	1150 2535	340 50	540AA	4PR
	NEW 265/35ZR20	99Y	9-9.5-10	9-9.5-10	9.5	7.6	271	694	775 1709	340 49	500 A A	4PR
	265/45ZR20	108W	8.5-9.0-10.0	/	9 J	8	266	746	1000 2205	340 49	500 A A	/
	265/50R20	111V	7.5-8.5-9.5	7.5-8.5-9.5	8 1/2J	8	277	774	1090 2403	340 49	500 A A	/
	275/30ZR20	97W	9.0-9.5-10.0	9.0-9.5-10.0	9 1/2J	8	278	674	730 1609	340 49	500 A A	/
	275/35ZR20	102W	9.0-9.5-11.0	9.0-9.5-11.0	9 1/2J	8	278	700	850 1874	340 49	500 A A	/
	275/40ZR20	106W	9.0-9.5-11.0	9.0-9.5-11.0	9 1/2 J	8.3	278	728	950 2094	340 49	500 A A	/
	275/50ZR20	113XL/Y	7.5-8.5-9.5	/	8 1/2J	8.3	284	784	1150 2535	340 50	500 A A	/
	285/30ZR20	99XL/Y	9.5-10.0-10.5	9.5-10.0-10.5	10J	8	290	680	775 1709	340 50	500 A A	/
	NEW 285/35ZR20	104XL/W	9.5-10.0-11.0	9.5-10.0-11.0	10J	8.3	290	708	900 1984	340 49	500 A A	/
	295/40ZR20	110XL/W	10.0-10.5-11.5	10.0-10.5-11.5	10 1/2J	8.3	301	744	1060 2337	340 49	500 A A	/
	NEW 295/45ZR20	114Y	9.5-10-10.5	9.5-10-10.5	10	7.8	296	774	1180 2601	340 49	500AA	4PR
	305/30ZR20	103XL/W	/	7.0-8.5-9.0	11 J	8.3	313	692	875 1929	340 49	500 A A	/
	NEW 305/35ZR20	107Y	10.5-11-11.5	10.5-11-11.5	11	7.8	313	722	975 2149	340 49	500 A A	4PR
	315/35ZR20	110W	10.5-11.0-12.5	10.5-11.0-12.5	11 J	8.3	320	728	1060 2337	340 49	500 A A	/
21"	NEW 245/35ZR21	96XL/Y	8.0-8.5-9.5	/	8 1/2J	8	248	705	710 1565	340 50	500 A A	/
	245/40ZR21	100Y	/	/	9.5	10	245	728	799 1763	330 49	320AA	4PR
	255/35ZR21	98Y	8.5-9-9.5	8.5-9-9.5	9	7.8	260	711	750 1653	340 49	500 A A	4PR
	255/40ZR21	105Y	8.5-9-9.5	8.5-9-9.5	9	7.8	260	737	925 2039	340 49	500 A A	4PR
	265/35ZR21	101XL/Y	9.0-9.5-10.5	/	9 1/2J	8	271	719	825 1819	340 50	500 A A	/
	265/40ZR21	105XL/Y	9.0-9.5-10.5	/	9 1/2J	8	271	745	925 2039	340 50	500 A A	/
	NEW 265/45ZR21	108Y	8.5-9-9.5	8.5-9-9.5	9	7.8	266	771	1000 2205	340 49	500 A A	4PR
	275/35ZR21	103XL/Y	9.0-9.5-11.0	/	9 1/2J	8	278	725	875 1929	340 50	500 A A	/
	275/40ZR21	109XL/Y	9.0-9.5-11.0	/	9 1/2J	8.3	278	753	1030 2271	340 50	500 A A	/
	275/45ZR21	110XL/Y	8.5-9.0-10.5	/	9J	8.3	273	781	1060 2337	340 50	500 A A	/

GRAND SPORT A/S

Wheel Dia.	TIRE SIZE	LOAD AND SPEED INDEX	EUROPEAN STANDARD RIM	AMERICAN STANDARD RIM	REC RIM WIDTH IN.	TREAD DEPTH MM	SECTION WIDTH MM	OVERALL DIAMETER MM	MAX LOAD KGS LBS	MAX INFLATION KPA PSI	UTQG	PLY RATING
21"	275/50ZR21	113Y	8-8.5-9	8-8.5-9	8.5	7.8	284	809	1150 2335	340 49	500 A A	4PR
	285/30ZR21	100Y	9.5-10-10.5	9.5-10-10.5	10	7.8	290	705	800 1764	340 49	500AA	4PR
	285/35ZR21	108XL/Y	9.5-10.0-11.0	/	10J	8.3	290	733	1000 2205	340 50	500 A A	/
	285/40ZR21	109XL/Y	9.5-10.0-11.0	/	10J	8.3	290	761	1030 2271	340 50	500 A A	/
	285/45ZR21	113XL/W	9.0-9.5-10.5	/	9 1/2J	8.3	285	789	1150 2535	340 50	500 A A	/
	295/35ZR21	107XL/Y	10.0-10.5-11.5	/	10 1/2J	8.3	301	739	975 2149	340 50	500 A A	/
	295/40ZR21	111XL/Y	10.0-10.5-11.5	/	10 1/2J	8.3	301	769	1090 2403	340 50	500 A A	/
	315/30ZR21	105XL/Y	10.5-11.0-11.5	/	11J	8.3	320	723	925 2039	340 50	500 A A	/
	315/35ZR21	111XL/Y	10.5-11.0-12.5	/	11J	8.3	320	753	1090 2403	340 50	500 A A	/
	315/40ZR21	111Y	10.5-11.0-12.5	/	11J	8.3	320	785	1090 2403	300 44	500 A A	/
	325/30ZR21	110XL/Y	11.0-11.5-12.0	/	11 1/2J	8.3	331	729	1060 2337	340 50	500 A A	/
	NEW 225/30ZR22	89W	7.5-8-8.5	7.5-8-8.5	8	7.8	230	695	545 1201	340 49	500 A A	4PR
	255/30ZR22	95W	8.5-9.0-9.5	/	9 J	8	260	713	690 1521	340 49	500 A A	/
22"	NEW 265/30ZR22	97W	9-9.5-10	9-9.5-10	9.5	7.8	271	719	730 1609	340 49	500AA	4PR
	265/35ZR22	102XL/W	9.0-9.5-10.5	/	9 1/2J	8	271	745	850 1874	340 49	500 A A	/
	275/35ZR22	107XL/Y	9.0-9.5-11.0	/	9 1/2J	8	278	751	975 2149	340 50	500 A A	/
	275/40ZR22	108XL/Y	9.0-9.5-11.0	/	9 1/2J	8.3	278	779	1000 2205	340 50	500 A A	/
	275/50R22	115XL/H	7.5-8.5-9.5	7.5-8.5-9.5	8 1/2J	8.3	284	835	1215 2679	340 50	500 A A	/
	285/35ZR22	106W	9.5-10.0-11.0	/	10J	8.3	290	759	950 2094	340 49	500 A A	/
	285/40ZR22	110XL/Y	9.5-10.0-11.0	/	10J	8.3	290	787	1060 2337	340 50	500 A A	/
	NEW 295/25ZR22	97Y	10-10.5-11	10-10.5-11	10.5	7.8	301	707	730 1609	340 49	500AA	4PR
	295/30ZR22	110XL/Y	10.0-10.5-11.0	/	10 1/2J	8.3	301	737	1060 2337	340 50	500 A A	/
	NEW 295/40ZR22	112W	/	/	11.5	9	295	795	1119 2469	340 50	420AA	4PR
	NEW 305/25ZR22	103Y	10.5-11-11.5	10.5-11-11.5	11	7.8	313	711	775 1709	340 49	500AA	4PR
	NEW 305/45R22	118V	9.5-10-10.5	9.5-10-10.5	10	7.8	303	833	1320 2910	340 49	500AA	4PR
	NEW 315/25ZR22	101Y	11-11.5-12	11-11.5-12	11.5	7.8	325	717	825 1819	340 49	500AA	4PR
	315/30ZR22	107XL/Y	10.5-11.0-11.5	/	11J	8.3	320	749	975 2149	340 50	500 A A	/
24"	315/35ZR22	111XL/Y	10.5-11.0-12.5	/	11J	8.3	320	779	1090 2403	340 50	500 A A	/
	325/40ZR22	114W	11-11.5-12	11-11.5-12	11.5	7.8	331	819	1180 2601	300 44	500AA	4PR
	NEW 245/30ZR24	94W	8-8.5-9	8-8.5-9	8.5	7.8	248	758	670 1477	340 49	500 A A	4PR
	NEW 255/25ZR24	95W	8.5-9-9.5	8.5-9-9.5	9	7.8	260	738	690 1521	340 49	500 A A	4PR
	NEW 255/30ZR24	97W	8.5-9-9.5	8.5-9-9.5	9	7.8	260	764	730 1609	340 49	500AA	4PR
	NEW 275/25ZR24	96W	9.5-10-10.5	9.5-10-10.5	10	7.8	283	748	710 1565	340 49	500AA	4PR
	NEW 285/30ZR24	103W	9.5-10-10.5	9.5-10-10.5	10	7.8	290	782	875 1929	340 49	500AA	4PR
	NEW 285/35ZR24	108W	9.5-10-10.5	9.5-10-10.5	10	7.8	290	810	1000 2205	340 49	500AA	4PR
26"	NEW 285/40R24	112V	9.5-10-10.5	9.5-10-10.5	10	7.8	290	838	1120 2469	340 49	500AA	4PR
	NEW 295/30ZR24	104Y	10-10.5-11	10-10.5-11	10.5	7.8	301	788	900 1984	340 49	500 A A	4PR
	NEW 295/35R24	110V	10-10.5-11	10-10.5-11	10.5	7.8	301	816	1060 2337	340 49	500AA	4PR
	NEW 305/30ZR24	107W	10.5-11-11.5	10.5-11-11.5	11	7.8	313	794	975 2149	340 49	500AA	4PR
26"	NEW 275/25ZR26	98W	9.5-10-10.5	9.5-10-10.5	10	7.8	283	798	750 1653	340 49	500AA	4PR
	NEW 295/25ZR26	102W	10-10.5-11	10-10.5-11	10.5	7.8	301	808	850 1874	340 49	500AA	4PR

Tire sizes, technical data and product availability are subject to change. Please see arroyotires.com for the most up-to-date information.





UHP All-Season
Ultra High Performance
GRAND SPORT 2




- Sizes – 13, 14, 15, 16, 17, 18, 19 & 20”
Rim Diameter 40, 45, 50, 55, 60, 65 & 70 Series Aspect Ratio
- 400 AA U.T.Q.G.
- 10/32 Tread Depth

- Features
Independent Tread Block
Pattern Spiral wound Joint
less Nylon Band
2 Wide Steel Belts

- Functions
Rapidly Removes Road Surface
Water. Increases strength in
high stress shoulder area
Reinforces the entire tread area

- Benefits
Increases contact to the road
for more traction.
Improves uniformity and ride
comfort.
Provides stability, excellent
wear character & long mileage



GRAND SPORT 2

Wheel Dia.	TIRE SIZE	SERVICE DESC./PLY RATING	OVERALL DIAMETER (in.)	SECTION WIDTH (in.)	APPROVED RIM (MEASURING RIM) WIDTH (in.)	TREAD DEPTH (in/32)	MAX LOAD (lbs)	MAX PSI	UTQG
12"	175/70R12	80T	-	-	-	-	-	-	-
13"	165/65R13	77H	21.34	6.81	5	10	908	44	400AA
	165/70R13	79T	21.89	6.61	5	10	963	44	400AA
	165/80R13	83T	-	-	-	-	-	-	-
	175/60R13	77H	-	-	-	-	-	-	-
	175/70R13	82H	22.60	6.93	5	10	1047	44	400AA
	185/60R13	80H	-	-	-	-	-	-	-
14"	185/70R13	86H	-	-	-	-	-	-	-
	165/60R14	75H	-	-	-	-	-	-	-
	165/70R14	-	-	-	-	-	-	-	-
	175/65R14	82H	22.99	7.56	5	10	1047	44	400AA
	175/65R14	86H XL	22.99	7.56	6.5	10	1168	50	400AA
	175/70R14	84H	23.70	7.64	5	10	1102	44	400AA
	175/70R14	88H XL	23.70	7.64	6.2	10	1235	50	400AA
	185/55R14	80V	21.73	7.64	6.7	10	992	44	400AA
	185/60R14	82V	22.76	7.68	5.5	10	1047	44	400AA
	185/65R14	86H	23.39	7.64	5.5	10	1168	44	400AA
	185/70R14	88H	23.94	7.39	5.5	10	1235	44	400AA
	195/45R14	77V	21.71	-	7	10	908	44	400AA
	195/70R14	91H	24.88	7.99	6.5	10	1356	44	400AA
	205/60R14	88H	-	-	-	-	-	-	-
15"	175/65R15	84H	24.82	-	6	10	1102	44	400AA
	185/55R15	82H	22.76	7.48	6.3	10	1047	44	400AA
	185/60R15	84V	23.39	7.47	5.5	10	1102	44	400AA
	185/60R15	88V XL	23.39	7.47	6.2	10	1235	50	400AA
	185/65R15	88H	24.46	7.99	5.5	10	1235	44	400AA
	185/65R15	92H XL	24.46	7.99	6.9	10	1389	50	400AA
	195/45R15	78V	22.01	7.87	6.5	10	937	44	400AA
	195/50R15	82V	22.91	8.07	6	10	1047	44	400AA
	195/55R15	89V XL	23.35	7.95	6	10	1279	50	400AA
	195/60R15	88V	24.21	8.23	6	10	1235	44	400AA
	195/65R15	95V XL	24.88	7.88	6	10	1521	50	400AA
	195/65R15	91V	24.77	7.88	6.2	10	1356	44	400AA
	205/60R15	95H XL	24.69	8.58	6	10	1521	50	400AA
	205/65R15	94V	25.59	8.66	6	10	1477	44	400AA

GRAND SPORT 2



GRAND SPORT 2

Wheel Dia.	TIRE SIZE	SERVICE DESC./PLY RATING	OVERALL DIAMETER (in.)	SECTION WIDTH (in.)	APPROVED RIM (MEASURING RIM) WIDTH (in.)	TREAD DEPTH (in/32)	MAX LOAD (lbs)	MAX PSI	UTQG
15"	205/65R15	99H XL	25.59	8.66	7	10	1709	50	400AA
	215/70R15	98H	27.01	8.98	7.5	10	1653	44	400AA
16"	185/60R16	86V	24.88	7.60	6.2	10	1168	44	400AA
	195/40R16	80V XL	22.01	7.87	7	10	992	50	400AA
	195/45ZR16	84W XL	22.91	7.87	6.5	10	1102	50	400AA
	195/55R16	87V	24.21	8.07	6	10	1202	44	400AA
	195/60R16	99V XL	25.16	7.88	6	10	1709	50	400AA
	205/40ZR16	83W XL	22.36	8.35	7.5	10	1074	50	400AA
	205/45ZR16	87W XL	23.15	8.35	7	10	1202	50	400AA
	205/55ZR16	94W XL	24.69	8.66	6.5	10	1477	50	400AA
	205/60R16	92V	25.59	8.66	6	10	1389	44	400AA
	205/65R16	95H	26.46	8.66	6	10	1521	44	400AA
	215/55ZR16	93W	25.04	9.25	7	10	1433	44	400AA
	215/55ZR16	97W XL	25.04	9.25	7.8	10	1609	50	400AA
	215/60R16	95H	26.30	8.94	6.5	10	1521	44	400AA
	215/60R16	99H XL	26.30	8.94	7.5	10	1709	50	400AA
	215/65R16	98H	27.01	8.98	6.5	10	1653	44	400AA
	225/55ZR16	95W	25.67	9.76	7	10	1521	44	400AA
	225/55ZR16	99W XL	25.67	9.76	7.5	10	1709	50	400AA
	225/60R16	98V	26.69	9.37	6.5	10	1653	44	400AA
	225/60R16	102V XL	26.69	9.37	6.5	10	1653	44	400AA
	225/60ZR16	102W XL	26.69	9.25	7.5	10	1874	50	400AA
	225/65R16	100H	27.56	9.29	7.5	10	1984	44	400AA
	225/65R16	104H XL	27.56	9.29	7.5	10	1984	50	400AA
17"	195/40R17	81V XL	22.91	7.87	7.5	10	1019	50	400AA
	205/40ZR17	84W XL	24.00	-	8	10	1102	46	400AA
	205/45ZR17	88W XL	24.17	8.35	7	10	1235	50	400AA
	205/50ZR17	93W XL	24.69	8.58	7	10	1433	50	400AA
	215/45R17	91V XL	24.65	8.82	7	10	1356	50	400AA
	215/45ZR17	91W XL	24.65	8.82	8	10	1356	50	400AA
	215/50ZR17	95W XL	25.04	9.29	7	10	1521	50	400AA
	215/55ZR17	94W	26.30	9.02	7	10	1477	44	400AA
	215/55ZR17	98W XL	26.30	9.02	7.7	10	1653	50	400AA
	225/45ZR17	94W XL	24.88	9.25	7.5	10	1477	50	400AA
	225/50ZR17	94W	25.67	9.37	8	10	1477	50	400AA

GRAND SPORT 2

Wheel Dia.	TIRE SIZE	SERVICE DESC./PLY RATING	OVERALL DIAMETER (in.)	SECTION WIDTH (in.)	APPROVED RIM (MEASURING RIM) WIDTH (in.)	TREAD DEPTH (in/32)	MAX LOAD (lbs)	MAX PSI	UTQG
17"	225/50ZR17	98W XL	25.67	9.37	7	10	1653	50	400AA
	225/55ZR17	97W	26.69	9.37	8	10	1521	44	400AA
	225/55ZR17	101W XL	26.69	9.37	7	10	1819	50	400AA
	225/60R17	99H	27.56	9.29	7.5	10	1709	44	400AA
	225/60R17	104H XL	27.56	9.29	7.5	10	1984	50	400AA
	225/65R17	102H	28.62	9.29	7.5	10	1874	44	400AA
	225/65R17	106H XL	28.62	9.29	7.5	10	2094	50	400AA
	235/45ZR17	97W XL	25.24	9.76	8	10	1609	50	400AA
	235/55R17	99V	27.17	10.04	5.5	10	1709	44	400AA
	235/60R17	106H XL	28.15	10.12	8.5	10	2094	50	400AA
	245/45ZR17	99W XL	25.63	9.76	7.5	10	1709	50	400AA
18"	225/40ZR18	92W XL	24.88	9.25	8	10	1389	50	400AA
	225/45ZR18	95W XL	25.87	9.25	7.5	10	1521	50	400AA
	225/50R18	-	-	-	-	-	-	-	-
	225/60R18	100V	28.62	9.25	6.5	10	1764	44	400AA
	235/40ZR18	95W XL	25.24	9.76	8.5	10	1521	50	400AA
	235/45R18	94V	26.26	9.76	8	10	1477	44	400AA
	235/45ZR18	94W	26.26	9.76	9	10	1477	44	400AA
	235/50ZR18	97W	27.17	10.04	8.5	10	1609	44	400AA
	235/55ZR18	100W	28.15	10.04	8.5	10	1764	44	400AA
	235/60R18	107V XL	30.16	9.69	8	10	2149	46	400AA
	235/65R18	106H XL	31.14	-	8	10	2094	46	400AA
	245/40ZR18	97W XL	25.63	9.76	8.5	10	1609	50	400AA
	245/45ZR18	96W	26.57	9.69	8.5	10	1510	44	400AA
	245/45ZR18	100W XL	26.57	9.69	8	10	1764	50	400AA
19"	225/40ZR19	99W XL	27.06	9.25	8.5	10	1433	50	400AA
	225/40ZR19	93W XL	26.98	10.16	9.5	10	1709	50	400AA
	225/55R19	99V	28.51	9.45	8	10	1709	44	400AA
	235/35ZR19	91W XL	25.24	9.49	8.9	10	1356	50	400AA
	235/35ZR19	91Y XL	25.24	9.49	8.9	10	1356	50	400AA
	235/40ZR19	96W XL	26.26	9.76	9	10	1565	50	400AA
	235/55R19	105V XL	29.17	9.72	8.5	10	2039	50	400AA
	245/40ZR19	94W	26.57	9.69	9	10	1477	44	400AA
20"	245/45ZR20	99W	28.66	9.65	8.5	10	1709	44	400AA

Tire sizes, technical data and product availability are subject to change. Please see arroyotires.com for the most up-to-date information.






UHP All-Season
Ultra High Performance
GRAND SPORT PLUS



NEW
Velvet / Suede
Sidewall Finish



- **Benefits**
Increases contact to the road for more traction.
Improves uniformity and ride comfort.
Provides stability, excellent wear character and long mileage
- **Functions**
Rapidly Removes Road Surface Water. Increases strength in high stress shoulder area Reinforces the entire tread area

GRAND SPORT PLUS

Wheel Dia.	TIRE SIZE	LOAD AND SPEED INDEX	REC RIM WIDTH IN.	TREAD DEPTH MM	SECTION WIDTH MM	OVERALL DIAMETER MM	MAX LOAD KGS LBS	MAX INFLATION KPA PSI	UTQG	PLY RATING
15"	185/55R15	86V XL	6.0	6.6	194	585	530 1168	340 50	400AA	4PR
	195/50R15	82V	6.0	6.6	201	577	475 1047	300 44	400AA	4PR
	195/55R15	85V	6.0	6.6	201	595	515 1135	300 44	400AA	4PR
16"	185/55R16	83H	6.0	6.6	194	610	487 1074	300 44	400AA	4PR
	195/45R16	84V XL	6.5	6.6	195	582	500 1102	340 50	400AA	4PR
	195/50R16	84V	6.0	6.6	201	602	500 1102	300 44	400AA	4PR
	195/55R16	87V	6.0	6.6	201	620	545 1201	300 44	400AA	4PR
	205/45ZR16	87W XL	7.0	6.6	206	590	545 1201	340 50	400AA	4PR
	205/50ZR16	91W XL	6.5	6.6	214	612	615 1356	340 50	400AA	4PR
	205/55ZR16	91W	6.5	6.6	214	632	615 1356	350 51	400AA	4PR
	215/55ZR16	97W XL	7.0	7	226	642	730 1609	340 50	400AA	4PR
	225/55ZR16	99W XL	7.0	7	233	654	775 1709	340 50	400AA	4PR
17"	205/45ZR17	88W XL	7.0	6.6	206	616	560 1235	340 50	400AA	4PR
	205/50ZR17	93W XL	6.5	6.6	214	638	650 1433	340 50	400AA	4PR
	205/55ZR17	95W XL	6.5	6.6	214	658	690 1521	340 50	400AA	4PR
	215/45ZR17	91W XL	7.0	7	213	626	615 1356	340 50	400AA	4PR
	215/50ZR17	95W XL	7.0	7	226	648	690 1521	340 50	400AA	4PR
	215/55ZR17	98W XL	7.0	7	226	668	750 1653	340 50	400AA	4PR
	225/45ZR17	91Y	7.5	7	225	634	615 1356	350 51	400AA	4PR
	225/50ZR17	98W XL	7.0	7	233	658	750 1653	340 50	400AA	4PR
	225/55ZR17	101W XL	7.0	7	233	680	825 1819	340 50	400AA	4PR
	235/45ZR17	97W XL	8.0	7	236	644	730 1609	340 50	400AA	4PR
	235/55ZR17	103W XL	7.5	7	245	690	875 1929	340 50	400AA	4PR
	245/40ZR17	95Y XL	8.5	7	248	628	690 1521	340 50	400AA	4PR
	245/45ZR17	99Y XL	8.0	7	243	652	775 1709	340 50	400AA	4PR
	215/40ZR18	89Y XL	7.5	7	218	629	580 1279	340 50	400AA	4PR
18"	215/45ZR18	93Y XL	7.0	7	213	651	650 1433	340 50	400AA	4PR
	215/55R18	99V XL	7.0	7	226	693	775 1709	340 50	400AA	4PR
	225/40ZR18	92W XL	8.0	7	230	637	630 1389	340 50	400AA	4PR
	225/45ZR18	95W XL	7.5	7	225	659	690 1521	340 50	400AA	4PR
	225/50ZR18	99W XL	7.0	7	233	683	775 1709	340 50	400AA	4PR
	225/55R18	98V	7.0	7	233	705	750 1653	350 51	400AA	4PR
	235/40ZR18	95Y XL	8.5	7	241	645	690 1521	340 50	400AA	4PR
	235/45ZR18	98Y XL	8.0	7	236	669	750 1653	340 50	400AA	4PR
	235/50ZR18	101W XL	7.5	7	245	693	825 1819	340 50	400AA	4PR
	235/55ZR18	104W XL	7.5	7	245	715	900 1984	340 50	400AA	4PR
	245/40ZR18	97Y XL	8.5	7	248	653	730 1609	340 50	400AA	4PR
	245/45ZR18	100Y XL	8.0	7	243	677	800 1764	340 50	400AA	4PR
	245/50ZR18	104W XL	7.5	7	253	703	900 1984	340 50	400AA	4PR

GRAND SPORT PLUS



UHP All-Season
Ultra High Performance

GRAND SPORT PLUS



NEW

Velvet / Suede
Sidewall Finish



• Benefits

- Increases contact to the road for more traction.
- Improves uniformity and ride comfort.
- Provides stability, excellent wear character and long mileage

• Functions

- Rapidly Removes Road Surface Water. Increases strength in high stress shoulder area Reinforces the entire tread area

GRAND SPORT PLUS

Wheel Dia.	TIRE SIZE	LOAD AND SPEED INDEX	REC RIM WIDTH IN.	TREAD DEPTH MM	SECTION WIDTH MM	OVERALL DIAMETER MM	MAX LOAD KGS LBS	MAX INFLATION KPA PSI	UTQG	PLY RATING
18"	255/35ZR18	94Y XL	9.0	7	260	635	670 1477	340 50	400AA	4PR
	255/55ZR18	109W XL	8.0	7	265	737	1030 2271	340 50	400AA	4PR
19"	225/40ZR19	93Y XL	8.0	7	230	663	650 1433	340 50	400AA	4PR
	225/45ZR19	96Y XL	7.5	7	225	685	710 1565	340 50	400AA	4PR
	225/55R19	99V	7.0	7	233	731	775 1709	350 51	400AA	4PR
	235/35ZR19	91Y XL	8.5	7	241	647	615 1356	340 50	400AA	4PR
	235/40ZR19	96Y XL	8.5	7	241	671	710 1565	340 50	400AA	4PR
	235/45ZR19	99Y XL	8.0	7	236	695	775 1709	340 50	400AA	4PR
	235/50ZR19	103W XL	7.5	7	245	719	875 1929	340 50	400AA	4PR
	235/55ZR19	105W XL	7.5	7	245	741	925 2039	340 50	400AA	4PR
	245/35ZR19	93Y XL	8.5	7	248	655	650 1433	340 50	400AA	4PR
	245/40ZR19	98Y XL	8.5	7	248	679	750 1653	340 50	400AA	4PR
	245/45ZR19	102Y XL	8.0	7	243	703	850 1874	340 50	400AA	4PR
	245/50ZR19	105Y XL	7.5	7	253	729	925 2039	340 50	400AA	4PR
	245/55ZR19	107W XL	7.5	7	253	753	975 2149	340 50	400AA	4PR
	255/35ZR19	96Y XL	9.0	7	260	661	710 1565	340 50	400AA	4PR
	255/40ZR19	100Y XL	9.0	7	260	687	800 1764	340 50	400AA	4PR
	255/55ZR19	111W XL	8.0	7	265	763	1090 2403	340 50	400AA	4PR
	265/50ZR19	110W XL	8.5	7	277	749	1060 2337	340 50	400AA	4PR
	275/30ZR19	96Y XL	9.5	7	278	649	710 1565	340 50	400AA	4PR
	275/35ZR19	100Y XL	9.5	7	278	675	800 1764	340 50	400AA	4PR
	275/40ZR19	105Y XL	9.5	7	278	703	925 2039	340 50	400AA	4PR
20"	235/55R20	102V	7.5	7	245	766	850 1874	350 51	400AA	4PR
	245/35ZR20	95Y XL	8.5	7	248	680	690 1521	340 50	400AA	4PR
	245/40ZR20	99Y XL	8.5	7	248	704	775 1709	340 50	400AA	4PR
	245/45ZR20	103Y XL	8.0	7	243	728	875 1929	340 50	400AA	4PR
	245/50ZR20	105W XL	7.5	7	253	754	925 2039	340 50	400AA	4PR
	255/45ZR20	105Y XL	8.5	7	255	738	925 2039	340 50	400AA	4PR
	255/50ZR20	109W XL	8.0	7	265	764	1030 2271	340 50	400AA	4PR
	255/55ZR20	110W XL	8.0	7	265	788	1060 2337	340 50	400AA	4PR
	265/45ZR20	108Y XL	9.0	7	266	746	1000 2205	340 50	400AA	4PR
	265/50ZR20	111W XL	8.5	7	277	774	1090 2403	340 50	400AA	4PR
	275/40ZR20	106Y XL	9.5	7	278	728	950 2094	340 50	400AA	4PR
	275/45ZR20	110Y XL	9.0	7	273	756	1060 2337	340 50	400AA	4PR
	275/50ZR20	113W XL	8.5	7	284	784	1150 2535	340 50	400AA	4PR
	315/35ZR20	110Y XL	11.0	7	320	728	1060 2337	340 50	400AA	4PR
21"	245/35ZR21	96Y XL	8.5	7	248	705	710 1565	340 50	400AA	4PR
	265/35ZR21	101Y XL	9.5	7	271	719	825 1819	340 50	400AA	4PR
	265/40ZR21	105Y XL	9.5	7	271	745	925 2039	340 50	400AA	4PR

GRAND SPORT PLUS



UHP All-Season
Ultra High Performance

GRAND SPORT PLUS



NEW
Velvet / Suede
Sidewall Finish



- Benefits
 - Increases contact to the road for more traction.
 - Improves uniformity and ride comfort.
 - Provides stability, excellent wear character and long mileage
- Functions
 - Rapidly Removes Road Surface Water. Increases strength in high stress shoulder area Reinforces the entire tread area

GRAND SPORT PLUS

Wheel Dia.	TIRE SIZE	LOAD AND SPEED INDEX	REC RIM WIDTH IN.	TREAD DEPTH MM	SECTION WIDTH MM	OVERALL DIAMETER MM	MAX LOAD KGS LBS	MAX INFLATION KPA PSI	UTQG	PLY RATING
21"	275/35ZR21	103Y XL	9.5	7	278	725	875 1929	340 50	400AA	4PR
	275/40ZR21	107Y XL	9.5	7	278	753	975 2149	340 50	400AA	4PR
	275/45ZR21	110Y XL	9.0	7	273	781	1060 2337	340 50	400AA	4PR
	285/35ZR21	105Y XL	10.0	7	290	733	925 2039	340 50	400AA	4PR
	285/40ZR21	109Y XL	10.0	7	290	761	1030 2271	340 50	400AA	4PR
	285/45ZR21	113Y XL	9.5	7	285	789	1150 2535	340 50	400AA	4PR
	295/35ZR21	107Y XL	10.5	7	301	739	975 2149	340 50	400AA	4PR
	295/40ZR21	111Y XL	10.5	7	301	769	1090 2403	340 50	400AA	4PR
	315/30ZR21	105Y XL	11.0	7	320	723	925 2039	340 50	400AA	4PR
	315/35ZR21	111Y XL	11.0	7	320	753	1090 2403	340 50	400AA	4PR
	315/40ZR21	115Y XL	11.0	7	320	785	1215 2679	340 50	400AA	4PR
	325/30ZR21	108Y XL	11.5	7	331	729	1000 2205	340 50	400AA	4PR
22"	275/35ZR22	104Y XL	9.5	7	278	751	900 1984	340 50	400AA	4PR
	275/40ZR22	107Y XL	9.5	7	278	779	975 2149	340 50	400AA	4PR
	275/50ZR22	115Y XL	8.5	7	284	835	1215 2679	340 50	400AA	4PR
	285/40ZR22	110Y XL	10.0	7	290	787	1060 2337	340 50	400AA	4PR
	315/30ZR22	107Y XL	11.0	7	320	749	975 2149	340 50	400AA	4PR
	315/35ZR22	111Y XL	11.0	7	320	779	1090 2403	340 50	400AA	4PR



NEW Velvet / Suede
Sidewall Finish

GRAND SPORT PLUS



TOURING
All - Season Tires
ECO PRO A/S




- Sizes - 14, 15, 16, 17 & 18" Rim
Diameters 60, 65 & 70 Series
Aspect Ratio
- 500 U.T.Q.G.
- 10/32 Tread Depth
- Uniquely Wide Flat Tread Radius
- Produces excellent steering progression and ride comfort.
- Jointless Nylon Band
- Increases strength in the high stress shoulder area.
- 2 Wide Steel Belts
- Strengthen the overall tread area.
- Provides stability, excellent wear character & long mileage.
- 9 more sizes on the way



PATTERN INTRODUCTIONS




4 wide longitudinal grooves provide good drainage performance, keep excellent handling performance in wet road.



Grooves with different thickness and sipes design can destroy water film to guarantee the drainage performance effectively , and reduce noise greatly , providing a comfortable driving experience.



The middle portion continuous strong tire tread ribs can improve the steering stability and straight performance at high speeds, to ensure stability and security.



Optimization of pitch width and sequence effectively reduce the noise resonance, resulting in a quieter ride.

ECO PRO A/S

Wheel Dia.	TIRE SIZE	LOAD AND SPEED INDEX	EUROPEAN STANDARD RIM	AMERICAN STANDARD RIM	REC RIM WIDTH IN.	TREAD DEPTH MM	SECTION WIDTH MM	OVERALL DIAMETER MM	MAX LOAD KGS LBS	MAX INFLATION KPA PSI	UTQG	PLY RATING
13"	NEW 165/65R13	77H	/	/	5	6.6	170	544	412 908	300 44	400A A	4PR
	NEW 175/60R13	77H	/	/	6	7.3	175	540	411 908	250 36	400A A	4PR
	NEW 175/70R13	82T	/	/	5	6.6	177	576	475 1047	300 44	400A A	4PR
	NEW 185/60R13	80H	/	/	6.5	7	185	551	450 992	300 44	400A A	4PR
14"	NEW 155/65R14	79H	/	/	4.5	6.6	157	558	387 853	300 44	400A A	4PR
	NEW 165/60R14	79H	/	/	6	7	165	554	387 963	250 51	400A A	4PR
	NEW 165/65R14	79H	4.5-5-5.5	4.5-5-5.5	5	7.4	170	570	437 963	300 44	500 A A	4PR
	NEW 165/70R14	81T	/	/	5	6.6	170	588	462 1019	300 44	400A A	4PR
	175/65R14	82H	5.0-6.0	5.0-6.0	5J	7.8	177	584	475 1047	300 44	500 A A	/
	175/70R14	88H	4.5-5.0-6.0	4.5-5.0-6.0	5J	7.8	177	602	560 1235	340 49	500 A A	/
	185/65R14	86H	5.0-5.5-6.5	5.0-5.5-6.5	5 1/2J	7.8	189	596	530 1168	300 44	500 A A	/
	185/70R14	88H	4.5-5.5-6.0	4.5-5.5-6.0	5 1/2J	7.8	189	616	560 1235	300 44	500 A A	/
	195/70R14	91H	5.0-6.0-6.5	5.0-6.0-6.5	6J	8	201	630	615 1356	300 44	500 A A	/
	205/70R14	98H	5.0-6.0-7.0	5.0-6.0-7.0	6J	8	209	644	750 1653	340 49	500 A A	/
15"	175/65R15	84H	5.0-6.0	5.0-6.0	5J	7.8	177	609	500 1102	300 44	500 A A	/
	185/60R15	84H	5.0-5.5-6.5	5.0-5.5-6.5	5 1/2J	7.8	189	603	500 1102	300 44	500 A A	/
	185/65R15	88H	5.0-5.5-6.5	5.0-5.5-6.5	5 1/2J	7.8	189	621	560 1235	300 44	500 A A	/
	195/60R15	88H	5.5-6.0-7.0	5.5-6.0-7.0	6J	8	201	615	560 1235	300 44	500 A A	/
	195/65R15	91H	5.5-6.0-7.0	5.5-6.0-7.0	6J	8	201	635	615 1356	300 44	500 A A	/
	195/65R15	91H	5.5-6-6.5	5.5-6-6.5	6	/	201	635	615 1356	300 44	500 A A	4PR
	205/60R15	91V	5.5-6.0-7.5	5.5-6.0-7.5	6J	8	209	627	615 1356	300 44	500 A A	/
	205/65R15	94H	5.5-6.0-7.5	5.5-6.0-7.5	6J	8	209	647	670 1477	300 44	500 A A	/
	205/70R15	96H	5.0-6.0-7.0	5.0-6.0-7.0	6J	8	209	669	710 1565	300 44	500 A A	/
	215/65R15	100H	6.0-6.5-7.5	6.0-6.5-7.5	6 1/2J	8	221	661	800 1764	340 49	500 A A	/
	215/70R15	98T	5.5-6.5-7.0	5.5-6.5-7.0	6 1/2J	8.3	221	683	750 1653	300 44	500 A A	/
16"	225/70R15	100T	6.0-6.5-7.5	6.0-6.5-7.5	6 1/2J	8	228	697	800 1764	300 44	500 A A	/
	185/60R16	86H	5.0-5.5-6.5	5.0-5.5-6.5	5 1/2J	7.8	189	628	530 1168	300 44	500 A A	/
	205/60R16	96V	5.5-6.0-7.5	5.5-6.0-7.5	6J	8	209	652	710 1565	340 49	500 A A	/
	205/65R16	95V	5.5-6.0-7.5	5.5-6.0-7.5	6J	7.8	209	672	690 1521	300 44	500 A A	/
	205/70R16	97H	5.0-6.0-7.0	5.0-6.0-7.0	6J	8	209	694	730 1609	300 44	500 A A	/
	215/60R16	95V	6.0-6.5-7.5	6.0-6.5-7.5	6 1/2J	8.3	221	664	690 1521	300 44	500 A A	/
	215/65R16	102H	6.0-6.5-7.5	6.0-6.5-7.5	6 1/2J	8	221	686	850 1874	340 49	500 A A	/
	225/60R16	98H	6.0-6.5-8.0	6.0-6.5-8.0	6 1/2J	8.3	228	676	750 1653	300 44	500 A A	/
	225/65R16	100H	6.0-6.5-8.0	6.0-6.5-8.0	6 1/2J	8	228	698	800 1764	300 44	500 A A	/
17"	235/65R16	107H	6.5-7.0-8.5	6.5-7.0-8.5	7J	8	240	712	975 2149	340 49	500 A A	/
	215/60R17	100H	6.0-6.5-7.5	6.0-6.5-7.5	6 1/2J	8	221	690	800 1764	340 49	500 A A	/
	215/65R17	99H	6.0-6.5-7.5	6.0-6.5-7.5	6 1/2J	8	221	712	775 1709	300 44	500 A A	/
18"	225/60R17	99V	6.0-6.5-8.0	6.0-6.5-8.0	6 1/2J	8.3	228	702	775 1709	300 44	500 A A	/
	225/60R18	104V	6.0-6.5-8.0	6.0-6.5-8.0	6 1/2J	8	228	727	900 1964	340 49	500 A A	/

Tire sizes, technical data and product availability are subject to change. Please see arroyotires.com for the most up-to-date information.



TOURING
All - Season Tires
ECO PRO PLUS

NEW

- Sizes - 13, 14, 15, 16, 17 & 18" Rim
- Uniquely Wide Flat Tread Radius
- Produces excellent steering progression and ride comfort.
- Increases strength in the high stress shoulder area.
- Strengthen the overall tread area.
- Provides stability, excellent wear character & long mileage.



ECO PRO PLUS

Wheel Dia.	TIRE SIZE	LOAD AND SPEED INDEX	REC RIM WIDTH IN.	TREAD DEPTH MM	SECTION WIDTH MM	OVERALL DIAMETER MM	MAX LOAD KGS LBS	MAX INFLATION KPA PSI	UTQG	PLY RATING
13"	155/65R13	73T	4.5	6.6	157	532	365 805	300 44	400AA	4PR
	155/70R13	75T	4.5	6.6	157	548	387 853	300 44	400AA	4PR
	155/80R13	79T	4.5	6.6	157	578	437 963	300 44	400AA	4PR
	165/65R13	77T	5.0	6.6	170	544	412 908	300 44	400AA	4PR
	165/70R13	79T	5.0	6.6	170	562	437 963	300 44	400AA	4PR
	175/70R13	82H	5.0	6.6	177	576	475 1047	300 44	400AA	4PR
	175/75R13	85T	5.0	6.6	177	592	515 1135	300 44	400AA	4PR
14"	155/65R14	75H	4.5	6.6	157	558	387 853	300 44	400AA	4PR
	165/65R14	79T	5.0	6.6	170	570	437 963	300 44	400AA	4PR
	165/70R14	81T	5.0	6.6	170	588	462 1019	300 44	400AA	4PR
	175/65R14	82H	5.0	6.6	177	584	475 1047	300 44	400AA	4PR
	175/70R14	84T	5.0	6.6	177	602	500 1102	300 44	400AA	4PR
	175/75R14	87T	5.0	6.6	177	618	545 1201	300 44	400AA	4PR
	185/60R14	82H	5.5	6.6	189	578	475 1047	300 44	400AA	4PR
	185/65R14	86H	5.5	6.6	189	596	530 1168	300 44	400AA	4PR
	185/70R14	88H	5.5	6.6	189	616	560 1235	300 44	400AA	4PR
	195/70R14	91T	6.0	6.6	201	630	615 1356	300 44	400AA	4PR
	205/60R14	88H	6.0	6.6	209	602	560 1235	350 51	400AA	4PR
15"	175/65R15	84H	5.0	6.6	177	609	500 1102	300 44	400AA	4PR
	185/60R15	84H	5.5	6.6	189	603	500 1102	300 44	400AA	4PR
	185/65R15	88H	5.5	6.6	189	621	560 1235	300 44	400AA	4PR
	195/60R15	88H	6.0	6.6	201	615	560 1235	300 44	400AA	4PR
	195/65R15	91H	6.0	6.6	201	635	615 1356	300 44	400AA	4PR
	205/65R15	94H	6.0	6.6	209	647	670 1477	350 51	400AA	4PR
16"	195/60R16	89V	6.0	6.6	201	640	580 1279	300 44	400AA	4PR
	205/60R16	92V	6.0	6.6	209	652	630 1389	350 51	400AA	4PR
	205/65R16	95H	6.0	6.6	209	672	690 1521	350 51	400AA	4PR
	215/60R16	95H	6.5	7	221	664	690 1521	350 51	400AA	4PR
	215/65R16	102V XL	6.5	7	221	686	850 1874	340 50	400AA	4PR
	225/60R16	102V XL	6.5	7	228	676	850 1874	340 50	400AA	4PR
	235/65R16	107H XL	7.0	7	240	712	975 2149	340 50	400AA	4PR
17"	215/65R17	103V XL	6.5	7	221	712	875 1929	340 50	400AA	4PR
	225/60R17	99H	6.5	7	228	702	775 1709	350 51	400AA	4PR
18"	225/60R18	100V	6.5	7	228	727	800 1764	350 51	400AA	4PR

ECO PRO PLUS



ARROYO RUN FLAT

16"	195/55R16	17"	205/45R17
	205/55R16		205/50R17
			205/55R17
			225/45R17
			225/50R17
			225/55R17

RUN FLAT



ARROYO RUN FLAT

18"	205/40R18	19"	225/40R19	20"	245/35R20
	225/40R18		225/45R19		245/40R20
	225/45R18		235/45R19		245/45R20
	225/50R18		235/55R19		255/45R20
	235/50R18		245/40R19		275/30R20
	235/55R18		245/45R19		275/35R20
	235/60R18	21"	245/50R19		275/40R20
	245/40R18		255/35R19		275/45R20
	245/45R18		255/50R19		315/35R20
	245/50R18		265/50R19		275/40R21
22"	255/35R18		275/35R19	22"	275/45R21
	255/40R18		275/40R19		285/35R21
					315/35R21

RUN FLAT



RUN FLAT 

HIGH STABILITY CANTERING RIB

The solid rib in the center of the tire ensures straight-line driving stability

WET GRIP GROOVE DESIGN

Four wide, longitudinal grooves channel road water, while lateral grooves work to direct it out from under the tire

LOW TREAD WEAR SHOULDER DESIGN

The shoulder is integrated with heat-resisting bars to keep the tread blocks stable and protect them from irregular wear. For the same reason, the design also improves high-speed cornering stability

FUEL-SAVING TREAD COMPOUND

The Arroyo Run Flat advanced tread compound reduces rolling resistance, which helps boost fuel efficiency and lower exhaust emissions

QUIET-RIDE PITCH ALIGNMENT

Optimized tread pitch width and alignment for quiet resonance and reduced road noise



RUN FLAT 

OPTIMIZED TREAD DESIGN

Our computer-aided design has optimized the tread pitch and alignment which reduces road noise levels at higher speeds

WET-GRIP SIPES AND GROOVES

Added sipes and grooves improve aquaplaning resistance and provide better handling on wet roads

DRY GRIP

Tread design creates a much larger contact area allowing better stability, cornering and control

ADVANCED TREAD COMPOUND

Advanced silica tread compound boosts rolling resistance and helps improve fuel efficiency

LATERAL AND LONGITUDINAL GROOVES

Deliver smooth handling and better control on dry and wet roads

Additional Sizes Coming Soon!



ALL-SEASON TOURING
S.U.V. & Crossover H/T Tires
ECO PRO H/T



- S.U.V. Sizes - 15, 16, 17, 18, 19 & 20"
Rim Diameters 55, 60, 65, 70 & 75 Series Aspect Ratio
- 600 U.T.Q.G.
- 10, 11 & 13/32 Tread Depth
- Uniquely Wide & Flat Tread
Radius Produces excellent steering progression and ride comfort.
- High Rubber to void ratio with variable shaped tread block elements.
Produces great wear character and long mileage.
Tread block noise is cancelled out creating sound comfort.
- Jointless Nylon Band
Spiral wound for uniformity
Increases strength in the high stress shoulder area.
- 2 Wide Steel Belts
Strengthen the overall tread area.
Provides stability, excellent wear character & long mileage.
- More sizes on the way



ECO PRO H/T

Wheel Dia.	TIRE SIZE	LOAD AND SPEED INDEX	EUROPEAN STANDARD RIM	AMERICAN STANDARD RIM	REC RIM WIDTH IN.	TREAD DEPTH MM	SECTION WIDTH MM	OVERALL DIAMETER MM	MAX LOAD KGS LBS	MAX INFLATION KPA PSI	UTQG	PLY RATING
15"	235/75R15	109T	6.0-6.5-8.0	6.0-6.5-8.0	6 1/2J	8.5	235	733	1030 2271	340 49	600 A B	/
	215/70R16	100H	5.5-6.5-7.0	5.5-6.5-7.0	6 1/2J	8.5	221	708	800 1764	300 44	600 A B	/
16"	LT215/85R16	115/112Q	5.5-6.0-7.0	5.5-6.0-7.0	6J	9.9	216	772	1215 2680	550 80	/	/
	225/70R16	103T	6.0-6.5-7.5	6.0-6.5-7.5	6 1/2J	8.5	228	722	875 1929	300 44	600 A B	/
	LT225/75R16	115/112S	6.0-7.0	6.0-7.5	6J	9.9	223	744	1215 2680	550 80	/	10 PR/E
	225/75R16	104T	/	7.5-8.5-10.0	6J	9.5	223	744	900 1984	300 44	600AB	/
	235/70R16	106H	6.0-7.0-8.0	6.0-7.0-8.0	7J	8.5	240	736	950 2094	300 44	600 A B	/
	LT235/85R16	120/116R	6.0-6.5-7.5	6.0-6.5-7.5	6 1/2J	9.9	235	806	1380 3042	550 80	/	10PR/LRE
	245/70R16	111T	6.5-7.0-8.0	6.5-7.0-8.0	7J	8.5	248	750	1090 2403	340 49	600 A B	/
	245/75R16	111T	6.5-7.0-8.0	6.5-7.0-8.0	7J	8.5	248	774	1090 2403	300 44	600 A B	/
	LT245/75R16	120/116S	/	6.5-7.0-8.0	7J	10.7	248	774	1380 3042	550 80	/	10 PR/E
	255/70R16	111T	6.5-7.5-8.5	6.5-7.5-8.5	7 1/2J	8.5	260	764	1090 2403	300 44	600 A B	/
	265/70R16	112H	7.0-8.0-9.0	7.0-8.0-9.0	8J	8.5	272	778	1120 2469	300 44	600 A B	/
	265/75R16	116T	7.0-7.5-9.0	7.0-7.5-9.0	7 1/2J	8.5	267	804	1250 2756	300 44	600 A B	/
	LT265/75R16	123/120R	/	7.0-7.5-9.0	7 1/2J	10.7	267	804	1550 3415	550 80	/	10PR/LRE
17"	225/65R17	102T	6.0-6.5-8.0	6.0-6.5-8.0	6 1/2J	8.5	228	724	850 1874	300 44	600 A B	/
	225/65R17	102T	6-6.5-7	6-6.5-7	6.5	/	228	724	850 1874	300 44	600AB	4PR
	235/65R17	108H	6.5-7.0-8.5	6.5-7.0-8.5	7J	8.5	240	738	1000 2205	340 49	600 A B	/
	235/65R17	108H	6.5-7-7.5	6.5-7-7.5	7	/	240	738	1000 2205	340 49	600AB	4PR
	LT235/80R17	120/117Q E-PLY		6.0-6.5-7.5	6 1/2J	9.9	235	808	1400 3085	550 80	/	10PR/LRE
	245/65R17	107H	7.0-8.5	7.0-8.5	7J	8.5	248	750	975 2149	300 44	600 A B	/
	245/70R17	114H	6.5-7.0-8.0	6.5-7.0-8.0	7J	8.5	248	776	1180 2601	340 49	600 A B	/
	LT245/70R17	119/116_S	/	6.5-7.0-8.0	7J	10.7	248	776	1360 2998	550 80	/	10PR/LRE
	LT245/75R17	121/118S	/	6.5-7.0-8.0	7 J	10.7	248	800	1450 3197	550 80	/	10 PR/E
	255/65R17	110H	7.0-7.5-9.0	7.0-7.5-9.0	7 1/2J	8.5	260	764	1060 2337	300 44	600 A B	/
	255/70R17	112H	6.5-7.5-8.5	6.5-7.5-8.5	7 1/2J	8.5	260	790	1120 2469	300 44	600 A B	/
	265/65R17	116H	7.5-8.0-9.5	7.5-8.0-9.5	8J	8.5	272	776	1250 2756	340 49	600 A B	/
	265/70R17	115H	7.0-8.0-9.0	7.0-8.0-9.0	8J	8.5	272	804	1215 2679	300 44	600 A B	/
	LT265/70R17	121/118S	/	7.0-8.0-9.0	8J	10.7	272	804	1450 3197	550 80	/	10 PR/E
18"	235/55ZR18	104W	6.5-7.5-8.5	6.5-7.5-8.5	7 1/2J	8.5	245	715	900 1984	340 49	600 A B	/
	235/60R18	107V	6.5-7.0-8.5	6.5-7.0-8.5	7J	8.5	240	739	975 2149	340 49	600 A B	/
	235/60R18	107V	6.5-7-7.5	6.5-7-7.5	7	/	240	739	975 2149	340 49	600AB	4PR

SIZES
COMING
SOON

Wheel Dia.	TIRE SIZE	Wheel Dia.	TIRE SIZE	Wheel Dia.	TIRE SIZE	Wheel Dia.	TIRE SIZE
16"	235/60R16	18"	285/60R18	20"	265/55R20	22"	265/50R22
17"	285/65R17	19"	265/55R19		285/50R20		275/45R22

Tire sizes, technical data and product availability are subject to change. Please see arroyotires.com for the most up-to-date information.



ALL-SEASON TOURING
S.U.V. & Crossover H/T Tires
ECO PRO H/T




ECO PRO H/T

Wheel Dia.	TIRE SIZE	LOAD AND SPEED INDEX	EUROPEAN STANDARD RIM	AMERICAN STANDARD RIM	REC RIM WIDTH IN.	TREAD DEPTH MM	SECTION WIDTH MM	OVERALL DIAMETER MM	MAX LOAD KGS LBS	MAX INFLATION KPA PSI	UTQG	PLY RATING
18"	235/65R18	110H	6.5-7.0-8.5	6.5-7.0-8.5	7J	8.5	240	763	1060 2337	340 49	600 A B	/
	245/60R18	105H	7.0-8.5	7.0-8.5	7J	8.5	248	751	925 2039	300 44	600 A B	/
	245/60R18	105H	6.5-7-7.5	6.5-7-7.5	7	/	248	751	925 2039	300 44	600 A B	4PR
	255/65R18	111T	7.0-7.5-9.0	7.0-7.5-9.0	7 1/2J	8.5	260	789	1090 2403	300 44	600 A B	/
	255/70R18	113H	6.5-7.5-8.5	6.5-7.5-8.5	7 1/2J	8.5	260	815	1150 2535	300 44	600 A B	/
	265/60R18	114V	7.5-8.0-9.5	7.5-8.0-9.5	8J	8.5	272	775	1180 2601	340 49	600 A B	/
	265/65R18	114H	7.5-8.0-9.5	7.5-8.0-9.5	8J	8.5	272	801	1180 2601	300 44	600 A B	/
	265/70R18	116H	7.0-8.0-9.0	7.0-8.0-9.0	8J	8.5	272	829	1250 2756	300 44	600 A B	/
	275/65R18	116H	7.5-8.0-9.5	7.5-8.0-9.5	8J	8.9	279	815	1250 2756	300 44	600 A B	/
	LT275/65R18	123/120_S	/	8.0-9.5	8J	11.5	279	815	1550 3417	550 80	/	10PR/LRE
	LT275/70R18	125/122_S	/	7.0-8.0-9.0	8J	11.7	279	843	1650 3638	550 80	/	10PR/LRE
19"	255/60R19	109H	7.0-7.5-9.0	/	7 1/2J	8.5	260	789	1030 2271	300 44	600 A B	/
20" NEW	245/50ZR20	102W	7.0-7.5-8.5	7.0-7.5-8.5	7 1/2J	8.5	253	754	850 1874	300 44	600 A B	/
	245/60R20	107H	/	7.0-8.5	7J	9.5	248	802	975 2149	300 44	600 A B	/
	265/60R20	112H	7.5-8-8.5	7.5-8-8.5	8	8.2	272	826	1120 2469	300 44	600 A B	4PR
	275/60R20	115V	7.5-8.0-9.5	7.5-8.0-9.5	8J	8.9	279	838	1215 2679	300 44	600 A B	/

Tire sizes, technical data and product availability are subject to change. Please see arroyotires.com for the most up-to-date information.


PATTERN INTRODUCTIONS




Four wide longitudinal grooves enhance water evacuation, improving cornering and handling performance on wet roads.

3 directional continuous center ribs ensure straight driving stability.

Cross-interlocking groove design provides reliable grip and reduces noise. Sharp edges of the lateral grooves cut through water film effectively, and resist hydroplaning of the tire.



Optimized depth of main grooves ensure high mileage. Optimal ratio of tread rib ensures efficient ground contact area while ensuring tire load carrying capacity. Depth of the shoulder grooves design, effectively reduce the tire heat, providing a reliable load durability.



Optimization of 5 variable pitch sequence, effectively reduces the noise resonance, improving comfort.

Optimized pitch width, effectively improves the load carrying capacity while reducing noise.



ALL-SEASON TOURING
S.U.V. & Crossover UHT Tires
CORSO UHT



NEW

• S.U.V. Sizes - 17, 19,20& 22"

- Uniquely Wide & Flat Tread Radius Produces excellent steering progression and ride comfort.
- High Rubber to void ratio with variable shaped tread block elements.
Produces great wear character and long mileage.
Tread block noise is cancelled out creating sound comfort.
- Jointless Nylon Band
Spiral wound for uniformity
Increases strength in the high stress shoulder area.
Strengthen the overall tread area.
Provides stability, excellent wear character & long mileage.



CORSO UHT

Wheel Dia.	TIRE SIZE	LOAD AND SPEED INDEX	REC RIM WIDTH IN.	TREAD DEPTH MM	SECTION WIDTH MM	OVERALL DIAMETER MM	MAX LOAD KGS LBS	MAX INFLATION KPA PSI	UTQG	PLY RATING
17" NEW	285/65R17	116T	8.5	7.8	292	802	1250 2756	350 51	500AA	4PR
19" NEW	265/55R19	109V	9.5	7	267	774	1030 2271	350 51	400AA	4PR
20" NEW	265/55R20	113V	9.5	10	267	774	1030 2271	350 51	360BA	4PR
	285/50R20	112V	9	7.8	297	794	1250 2756	340 50	500AA	4PR
22" NEW	265/50R22	112H	10.5	10	267	823	1120 2469	340 50	600BA	4PR

Tire sizes, technical data and product availability are subject to change. Please see arroyotires.com for the most up-to-date information.



CORSO UHT



ALL-SEASON TOURING
S.U.V. & Crossover H/T Tires

ECO PRO H/T PLUS



NEW

- S.U.V. Sizes - 15, 16, 17, 18, 19,20,21 & 22"
- Uniquely Wide & Flat Tread Radius Produces excellent steering progression and ride comfort.
- High Rubber to void ratio with variable shaped tread block elements.
Produces great wear character and long mileage.
Tread block noise is cancelled out creating sound comfort.
- Jointless Nylon Band
Spiral wound for uniformity
Increases strength in the high stress shoulder area.
Strengthen the overall tread area.
Provides stability, excellent wear character & long mileage.



ECO PRO H/T PLUS

Wheel Dia.	TIRE SIZE	LOAD AND SPEED INDEX	REC RIM WIDTH IN.	TREAD DEPTH MM	SECTION WIDTH MM	OVERALL DIAMETER MM	MAX LOAD KGS LBS	MAX INFLATION KPA PSI	UTQG	PLY RATING
15"	255/70R15	112H XL	7.5	7.8	260	739	1120 2469	340 50	500AA	4PR
	215/70R16	100H	6.5	7.8	221	708	800 1764	350 51	500AA	4PR
16"	265/70R16	112H	8.0	7.8	272	778	1120 2469	350 51	500AA	4PR
	215/60R17	100V XL	6.5	7.8	221	690	800 1764	340 50	500AA	4PR
17"	225/65R17	102V	6.5	7.8	228	724	850 1874	350 51	500AA	4PR
	235/60R17	106H XL	7.0	7.8	240	714	950 2094	340 50	500AA	4PR
	235/65R17	108V XL	7.0	7.8	240	738	1000 2205	340 50	500AA	4PR
	245/65R17	111H XL	7.0	7.8	248	750	1090 2403	340 50	500AA	4PR
	245/70R17	110H	7.0	7.8	248	776	1060 2337	350 51	500AA	4PR
	265/65R17	112H	8.0	7.8	272	776	1120 2469	350 51	500AA	4PR
	265/70R17	115H	8.0	7.8	272	804	1215 2679	350 51	500AA	4PR
	285/65R17	116H	8.5	7.8	292	802	1250 2756	350 51	500AA	4PR
	LT265/70R17	121/118S	8.0	9.5	272	804	1450 3195	550 80	-	10PR
	235/60R18	107V XL	7.0	7.8	240	739	975 2149	340 50	500AA	4PR
18"	235/65R18	110H XL	7.0	7.8	240	763	1060 2337	340 50	500AA	4PR
	245/60R18	105H	7.0	7.8	248	751	925 2039	350 51	500AA	4PR
	255/65R18	111H	7.5	7.8	260	789	1090 2403	350 51	500AA	4PR
	265/60R18	110H	8.0	7.8	272	775	1060 2337	350 51	500AA	4PR
	265/65R18	114H	8.0	7.8	272	801	1180 2601	350 51	500AA	4PR
	265/70R18	116H	8.0	7.8	272	829	1250 2756	350 51	500AA	4PR
	285/60R18	120H XL	8.5	7.8	292	799	1400 3086	340 50	500AA	4PR
	275/55R20	113V	8.5	7.8	284	810	1150 2535	350 51	500AA	4PR
20"	275/60R20	116H XL	8.0	7.8	279	838	1250 2756	340 50	500AA	4PR
	285/50R20	116V XL	9.0	7.8	297	794	1250 2756	340 50	500AA	4PR
	275/50R21	113V XL	8.5	7.8	284	809	1150 2535	340 50	500AA	4PR
21"	275/50R21	113V XL	8.5	7.8	284	809	1150 2535	340 50	500AA	4PR
22"	285/45R22	114V XL	9.5	7.8	285	815	1180 2601	340 50	500AA	4PR

Tire sizes, technical data and product availability are subject to change. Please see arroyotires.com for the most up-to-date information.



ECO PRO H/T PLUS



ALL-SEASON TOURING
S.U.V. & Crossover H/T Tires

ECO PRO H/T2



- S.U.V. Sizes - 15, 16, 17, 18 & 20"
Rim Diameters 55, 60, 65, 70 & 75 Series Aspect Ratio
- 600 U.T.Q.G.
- 10, 11 & 12/32 Tread Depth
- Uniquely Wide & Flat Tread Radius
Produces excellent steering progression and ride comfort.
- High Rubber to void ratio with variable shaped tread block elements. Produces great wear characteristics and long mileage. Tread block noise is cancelled out creating sound comfort.
- Jointless Nylon Band
Spiral wound for uniformity
Increases strength in the high stress shoulder area.
- 2 Wide Steel Belts
Strengthen the overall tread area. Provides stability, excellent wear character & long mileage.
- More sizes on the way



ECO PRO H/T2

Wheel Dia.	TIRE SIZE	SERVICE DESC./PLY RATING	OVERALL DIAMETER (in.)	SECTION WIDTH (in.)	APPROVED RIM (MEASURING RIM) WIDTH (in.)	TREAD DEPTH (in/32)	MAX LOAD (lbs)	MAX PSI	UTQG
15"	235/75R15	105S	29.06	9.69	7.7	11	2039	46	600AA
16"	225/65R16	100H	27.56	9.06	7.5	11	1764	46	600AA
	235/70R16	106T	29.06	9.65	7.5	12	2094	46	600AA
	LT225/75R16	115/112S	29.29	10.47	7.5	12	2680/2470	80	-
	LT245/75R16	120/116S	30.51	9.88	7.5	12	3042/2778	80	-
	LT265/75R16	123/120S	31.65	10.55	8.5	12	3415/3085	80	-
17"	225/60R17	99H	27.56	9.02	7.5	11	1709	46	600AA
	225/65R17	102H	28.46	9.06	7.5	11	1874	46	600AA
	235/65R17	104H	29.06	9.65	7.7	11	1984	46	600AA
	245/65R17	111T XL	29.53	9.82	8	11	2149	51	600AA
	265/70R17	115T	31.65	10.63	8.5	11	2680	46	600AA
	LT245/70R17	119/116S	30.51	9.88	8	12	3000/2755	80	-
	LT245/75R17	121/118S	31.50	8.09	7.5	12	3195/2910	80	-
	LT265/70R17	121/118S	31.65	10.63	8.5	12	3195/2910	80	-
18"	235/60R18	107V XL	29.06	9.65	7.7	11	2149	51	600AA
	235/65R18	106H	30.00	9.57	7.7	11	2094	46	600AA
	245/60R18	105H	29.53	9.76	8	11	2039	46	600AA
	LT275/70R18	125/122S	33.19	10.98	8.5	12	3640/3305	80	-
20"	275/55R20	117H XL	31.81	11.06	9.3	11	2833	51	600AA

Tire sizes, technical data and product availability are subject to change. Please see arroyotires.com for the most up-to-date information.

PATTERN INTRODUCTIONS



Arroyo Eco Pro H/T2 is a Highway Terrain tire for crossover, sport utility & light truck vehicles. It brings performance and durability while providing style and comfort and gives you grip throughout all seasons. These tires are characterized by their sturdy design, chip-resistant compound which extends its tread life. Its tread groove design helps to improve traction during wet road and winter season conditions. The heavier duty sizes are built to give a better grip during heavy load conditions. Ride comfort is provided with the internal composition of rubber below the tread. Its structure is built on ultra high strength steel belts strengthened with spirally wrapped nylon yielding excellent braking and stability.





UHP All-Season
Ultra High Performance

ULTRA SPORT A/S



- S.U.V. Sizes - 19, 20, 22, 24 & 26" Rim Diameters 30, 35, 40, 45, 50, & 55 Series Aspect Ratio
- 500 U.T.Q.G.
- 10/32 Tread Depth
- Uniquely Wide & Flat Tread Radius Produces excellent steering progression and ride comfort.
- Aggressive "Grown-Up" tread design. Produces great traction for all weather and road surfaces. Tightly packed shoulder blocks are quiet and wear evenly.
- Jointless Nylon Band Spiral wound for uniformity Increases strength in the high stress shoulder area.
- 2 Wide Steel Belts Strengthen the overall tread area. Provides stability, excellent wear character & long mileage.



ULTRA SPORT A/S

Wheel Dia.	TIRE SIZE	LOAD AND SPEED INDEX	EUROPEAN STANDARD RIM	AMERICAN STANDARD RIM	REC RIM WIDTH IN.	TREAD DEPTH MM	SECTION WIDTH MM	OVERALL DIAMETER MM	MAX LOAD KGS LBS	MAX INFLATION KPA PSI	UTQG	PLY RATING
19"	255/50ZR19	107Y	7.0-8.0-9.0	7.0-8.0-9.0	8J	8	265	739	975 2149	340 49	500 A A	/
20"	275/45R20	110V	8.5-9.0-10.5	8.5-9.0-10.5	9J	8.3	273	756	1060 2337	340 49	500 A A	/
	275/55R20	117V	7.5-8.5-9.5	7.5-8.5-9.5	8 1/2J	8.3	284	810	1285 2833	340 49	500 A A	/
22"	235/30ZR22	90W	8.5	/	8 1/2J	8	241	701	600 1323	340 49	500 A A	/
	245/30ZR22	95W	8.0-8.5-9.0	/	/	/	/	/	690 1521	340 49	500 A A	/
	265/35ZR22	102W	9.0-9.5-10.5	9.0-9.5-10.5	9 1/2J	8	271	745	850 1874	340 49	500 A A	/
	265/40ZR22	106W	9.0-9.5-10.5	/	9 1/2J	8	271	771	950 2094	340 49	500 A A	/
	285/45R22	114V	9.0-9.5-10.5	9.0-9.5-10.5	9 1/2 J	8.3	285	815	1180 2601	340 49	500 A A	/
	305/40R22	114V	10.0-11.0-12.0	10.0-11.0-12.0	11J	8.3	313	803	1180 2601	340 49	500 A A	/
24"	295/35ZR24	110W	10.0-10.5-11.5	/	10 1/2J	8.3	301	816	1060 2337	340 49	500 A A	/
	305/35R24	112V	10.0-11.0-12.0	10.0-11.0-12.0	11J	8.3	313	824	1120 2469	340 49	500 A A	/
26"	295/30ZR26	107W	10.0-10.5-11.0	/	10 1/2 J	8.3	301	838	975 2149	340 49	500 A A	/
	305/30ZR26	109V	10.5-11.0-11.5	/	11J	8.3	313	844	1030 2271	340 49	500 A A	/

Tire sizes, technical data and product availability are subject to change. Please see arroyotires.com for the most up-to-date information.

PATTERN INTRODUCTIONS



Central longitudinal continuous main rib, provides straight driving stability and high speed controllability ensuring safety. Twin longitudinal main grooves with 3D groove walls are effective in preventing hydroplaning on wet roads, and reduce noise. Continuous blocks ensure efficient ground contact area, providing extreme control and stability.



Zig Zag grooves, cross grooves and sipes improve the all-weather performance of the tire.



With the advanced design concept silica compound and 3D sips distribution ULTRA SPORT A/S provides reliable grip and excellent braking performance in wet and dry conditions.



Optimization of variable random pitch sequence, minimizes noise generation contributing a quiet and comfortable ride.



ULTRA SPORT A/S



UHP All-Season
Ultra High Performance

RAZZO SPORT A/S



NEW

- 500 U.T.Q.G.
- 10/32 Tread Depth
- Uniquely Wide & Flat Tread Radius Produces excellent steering progression and ride comfort.
- Aggressive "Grown-Up" tread design. Produces great traction for all weather and road surfaces. Tightly packed shoulder blocks are quiet and wear evenly.
- Jointless Nylon Band Spiral wound for uniformity Increases strength in the high stress shoulder area.
- 2 Wide Steel Belts Strengthen the overall tread area. Provides stability, excellent wear character & long mileage.



RAZZO SPORT A/S

Wheel Dia.	TIRE SIZE	LOAD AND SPEED INDEX	EUROPEAN STANDARD RIM	AMERICAN STANDARD RIM	REC RIM WIDTH IN.	TREAD DEPTH MM	SECTION WIDTH MM	OVERALL DIAMETER MM	MAX LOAD KGS LBS	MAX INFLATION KPA PSI	UTQG	PLY RATING
20" NEW	275/55R20	117V	7.5-8.5-9.5	7.5-8.5-9.5	8 1/2J	8.1	284	810	1285 2833	340 50	500 A A	/
22" NEW	285/45R22	114V	9.0-9.5-10.5	9.0-9.5-10.5	9 1/2J	7.9	285	815	1180 2601	340 50	500 A A	/
NEW	305/40R22	114V	10.0-11.0-12.0	10.0-11.0-12.0	11J	7.9	313	803	1180 2601	340 50	500 A A	/
24" NEW	305/35R24	112V	10.0-11.0-12.0	10.0-11.0-12.0	11J	7.9	313	824	1120 2469	340 50	500 A A	/

Tire sizes, technical data and product availability are subject to change. Please see arroyotires.com for the most up-to-date information.

NEW SIZES COMING SOON



RAZZO SPORT A/S



RAZZO SPORT A/S



ULTRA SPORT **A/S**



HIGHWAY-COMMERCIAL
All-Season Tires
VAN PRO 2



- Symmetrical/Non-Directional Commercial Hwy A/S
- Speed Ratings – Q, R – 6 PR
- 65-75 Series, 12-14-16 in. rim sizes
- 4 Wide Circumferential Ribs for outstanding strength and load support
- 3 Zigzag Circumferential grooves for water evacuation and all-season traction.
- Made in the European Union
- Designed for drivers of commercial pick-up trucks and vans for rugged all-season commercial use



HIGHWAY-COMMERCIAL
All-Season Tires
VAN PRO 3



- Symmetrical/Non-Directional Commercial Hwy A/S
- Speed Ratings – Q, R – 6 PR
- 65-75 Series, 14-16 in. rim sizes
- 4 Wide Circumferential Ribs for outstanding strength and load support
- 3 Zigzag Circumferential grooves for water evacuation and all-season traction.
- Made in the European Union
- Designed for drivers of commercial pick-up trucks and vans for rugged all-season commercial use



VAN PRO 2

Wheel Dia.	TIRE SIZE	SERVICE DESC./PLY RATING	OVERALL DIAMETER (in.)	SECTION WIDTH (in.)	APPROVED RIM (MEASURING RIM) WIDTH (in.)	TREAD DEPTH (in/32)	MAX LOAD (lbs)	MAX PSI	UTQG
12"	5.00R12C	-	-	-	-	-	-	-	-
14"	185R14C	102/100Q	25.51	7.52	5.5	10	1874/1764	65	-
	195R14C	-	-	-	-	-	-	-	-
	205/75R14C	-	-	-	-	-	-	-	-
15"	195/70R15C	104/102R	25.71	7.87	6.5	12	1984/1874	65	-
	195R15C	-	-	-	-	-	-	-	-
	205/70R15C	-	-	-	-	-	-	-	-
	215/70R15C	-	-	-	-	-	-	-	-
	225/70R15C	-	-	-	-	-	-	-	-
16"	195/75R16C	-	-	-	-	-	-	-	-
	195/75R16C	107/105R	27.17	7.64	5.5	12	2150/2039	69	-
	205/65R16C	-	-	-	-	-	-	-	-
	205/75R16C	-	-	-	-	-	-	-	-
	215/65R16C	-	-	-	-	-	-	-	-
	215/75R16C	-	-	-	-	-	-	-	-
	225/65R16C	-	-	-	-	-	-	-	-
	235/65R16C	121/119Q	27.99	9.45	7	12	3197/2998	83	-

Tire sizes, technical data and product availability are subject to change. Please see arroyotires.com for the most up-to-date information.

VAN PRO 3

Wheel Dia.	TIRE SIZE	SERVICE DESC./PLY RATING	OVERALL DIAMETER (in.)	SECTION WIDTH (in.)	APPROVED RIM (MEASURING RIM) WIDTH (in.)	TREAD DEPTH (in/32)	MAX LOAD (lbs)	MAX PSI	UTQG
14"	195R14C	106/104R	26.22	7.9	6	12	2094/1984	65	-
	205R14C	-	-	-	-	-	-	-	-
	215R14C	-	-	-	-	-	-	-	-
16"	195/75R16C	107/105R	27.48	8.3	6.5	12	2150/2039	69	-
	235/65R16C	121/119Q	27.99	9.4	8	12	3197/2998	83	-

Tire sizes, technical data and product availability are subject to change. Please see arroyotires.com for the most up-to-date information.



HIGHWAY-COMMERCIAL
All-Season Tires
VAN PRO



- Symmetrical/Non-Directional Commercial Hwy A/S
- Speed Ratings – Q, R – 6 PR
- 65-75 Series, 16 in. rim size
- 4 Wide Circumferential Ribs for outstanding strength and load support
- 3 Zigzag Circumferential grooves for water evacuation and all-season traction.
- Made in Thailand
- Designed for drivers of commercial pick-up trucks and vans for rugged all-season commercial use



VAN PRO

Wheel Dia.	TIRE SIZE	LOAD AND SPEED INDEX	EUROPEAN STANDARD RIM	AMERICAN STANDARD RIM	REC RIM WIDTH IN.	TREAD DEPTH MM	SECTION WIDTH MM	OVERALL DIAMETER MM	MAX LOAD KGS LBS	MAX INFLATION KPA PSI	UTQG	PLY RATING
13" NEW	165R13C	94/93R	/	/	4.5	7	167	596	670 1477	450 65	/	8PR
14" NEW	185R14C	102/100Q	/	/	5.5	7.8	188	650	850 1874	450 65	/	8PR
14" NEW	195R14C	106/104S	/	/	5.5	7.8	198	666	950 2094	450 65	/	8PR
15" NEW	185/60R15C	94/92T	5-5.5-6	5-5.5-6	5.5	8.5	189	603	670 1477	375 55	/	6PR
	195/70R15C	104/102R	/	/	6	7.8	201	655	900 1984	450 65	/	8PR
	195R15C	106/104S	/	/	5.5	7.8	198	690	950 2094	450 65	/	8PR
	205/70R15C	106/104S	/	/	6	8.3	209	669	950 2094	450 65	/	8PR
	215/70R15C	106/104S	/	/	6.5	8.3	221	683	1030 2271	450 65	/	8PR
	225/70R15C	112/110S	/	/	7.5	8.7	225	696	1119 2469	450 65	/	8PR
16"	195/75R16C	110/108R 10PLY	5.0-5.5-6.0	/	5 1/2J	8.8	196	698	1060 2335	525 77	/	10PR/LRE
	235/65R16C	121/119R 10PLY	6.5-7.0-7.5	/	7J	8.8	240	712	1450 3195	575 83	/	10PR/LRE
	285/65R16C	COMING SOON										

Tire sizes, technical data and product availability are subject to change. Please see arroyotires.com for the most up-to-date information.

HIGHWAY-COMMERCIAL
All-Season Tires
VAN PRO PLUS NEW



- Symmetrical/Non-Directional Commercial Hwy A/S
- Speed Ratings – Q, R – 6 PR
- 65-75 Series, 16 in. rim size
- 4 Wide Circumferential Ribs for outstanding strength and load support
- 3 Zigzag Circumferential grooves for water evacuation and all-season traction.
- Made in China
- Designed for drivers of commercial pick-up trucks and vans for rugged all-season commercial use



VAN PRO PLUS

Wheel Dia.	TIRE SIZE	LOAD AND SPEED INDEX	REC RIM WIDTH IN.	TREAD DEPTH MM	SECTION WIDTH MM	OVERALL DIAMETER MM	MAX LOAD KGS LBS	MAX INFLATION KPA PSI	UTQG	PLY RATING
13"	155R13C	90/88S	4.5	7	157	578	600 1323	450 65	/	8PR
	165R13C	94/93R	4.5	7	167	596	670 1477	450 65	/	8PR
14"	175/65R14C	90/88T	5.0	7.8	177	584	600 1323	375 54	/	6PR
	175/70R14C	95/93T	5.0	7.8	177	602	690 1521	375 54	/	6PR
	185R14C	102/100S	5.5	7.8	188	650	850 1874	450 65	/	8PR
	195R14C	106/104S	5.5	7.8	198	666	950 2094	450 65	/	8PR
15"	195/70R15C	104/102S	6.0	7.8	201	655	900 1984	450 65	/	8PR
	195R15C	106/104S	5.5	7.8	198	690	950 2094	450 65	/	8PR
	205/70R15C	106/104S	6.0	8.3	209	669	950 2094	450 65	/	8PR
	215/70R15C	109/107T	6.5	8.3	221	683	1030 2271	450 65	/	8PR
16"	195/75R16C	107/105S	5.5	7.8	196	698	975 2149	475 69	/	8PR
	205/65R16C	107/105T	6.0	8.3	209	672	975 2149	475 69	/	8PR
	215/65R16C	109/107T	6.5	8.3	221	686	1030 2271	475 69	/	8PR
	225/65R16C	112/110T	6.5	8.3	228	698	1120 2469	475 69	/	8PR
	235/65R16C	121/119R	7.0	8.3	240	712	1450 3197	575 83	/	10PR

Tire sizes, technical data and product availability are subject to change. Please see arroyotires.com for the most up-to-date information.



TAMAROCK A/T

SUV Metric Sizes - LT Metric & High Float Sizes 15, 16, 17, 18, 20 & 22" Rim Diameters 40, 45, 55, 60, 70 & 75 Series Aspect Ratios 12, 13, 15, 16 & 17/32 Tread Depth Super Wide & Flat Tread Radius Produces excellent steering progression and ride comfort. Attractive Marked Tread Design Produces great traction for all weather and road surfaces. Wrap around shoulder elements are profound and functional. Jointless Nylon Band Spiral wound for uniformity Increases strength in the high stress shoulder area. 2 Wide Steel Belts Strengthen the overall tread area. Provides stability, excellent wear character & long mileage.




LONGER
TREAD LIFE



STRONGER
SIDEWALL



QUIETER
RIDE



ARROYO
TIRES

ATTACK ANY TERRAIN WITH CONFIDENCE



ALL-TERRAIN TAMAROCK A/T TIRES

ARROYOTIRES.COM



ALL-TERRAIN
Tamarock A/T Tires
TAMAROCK A/T



- SUV Metric Sizes - LT Metric & High Float Sizes 15, 16, 17, 18, 20 & 22" Rim Diameters
- 40, 45, 55, 60, 70 & 75 Series Aspect Ratios
- 12, 13, 15,16 & 17/32 Tread Depth
- Super Wide & Flat Tread Radius Produces excellent steering progression and ride comfort.
- Attractive Marked Tread Design Produces great traction for all weather and road surfaces. Wrap around shoulder elements are profound and functional.
- Jointless Nylon Band Spiral wound for uniformity Increases strength in the high stress shoulder area.
- 2 Wide Steel Belts Strengthen the overall tread area. Provides stability, excellent wear character & long mileage.



PATTERN INTRODUCTIONS



- Strong Pattern Block Design Strong central pattern blocks ensure stable handling performance and powerful control force under off-road conditions. Rugged blocks can prevent cutting, scratching and impact damage.
- Solid Square Shoulder Strong shoulder provide adequate dry traction and turning performance.



- Excellent Drainage Performance Four wide longitudinal grooves can evacuate water effectively, enhance handling and steering on wet road surface .
- Special Multi-Angle Sipe Design Irregular sipes design can reduce noise and improve grip on snow-covered roads effectively, to ensure excellent control performance.

TAMAROCK A/T

Wheel Dia.	TIRE SIZE	LOAD AND SPEED INDEX	EUROPEAN STANDARD RIM	AMERICAN STANDARD RIM	REC RIM WIDTH	TREAD DEPTH MM	SECTION WIDTH MM	OVERALL DIAMETER MM	MAX LOAD KGS LBS	MAX INFLATION KPA PSI	UTQG	PLY RATING
15"	31x10.50R15LT	109S	/	7.0-8.5-9.0	8 1/2J	12.8	268	775	1030 2270	350 50	/	6PR/LRC
16"	NEW 205R16C	110/108Q	/	/	6	11.4	207	740	1059 2335	440 65	/	8PR
	LT245/75R16	120/116R	/	6.5-7.0-8.0	7J	12.8	248	774	1380 3042	550 80	/	10PR/LRE
	265/70R16	112T	7.0-8.0-9.0	7.0-8.0-9.0	8J	10.4	272	778	1120 2469	300 44	500 A A	/
	NEW 275/70R16	114S	/	/	8.5	13	275	792	1179 2601	300 44	500AB	4PR
	LT265/75R16	123/120R	/	7.0-7.5-9.0	7 1/2J	12.8	267	804	1550 3415	550 80	/	10PR/LRE
17"	LT285/75R16	126/123R	/	7.5-8.0-9.5	8J	13.7	286	834	1700 3750	550 80	/	10PR/LRE
	NEW 225/65R17	102T	6-6.5-7	6-6.5-7	6.5	10	228	724	850 1874	300 44	500 A A	4PR
	NEW 235/65R17	104T	6.5-7-7.5	6.5-7-7.5	7	10	240	738	900 1984	300 44	500 A A	4PR
	LT245/75R17	121/118_S	/	6.5-7.0-8.0	7J	12.8	248	800	1450 3195	550 80	/	10PR/LRE
	245/75R17	110H	6.5-7.0-8.0	6.5-7.0-8.0	7J	10.4	248	800	1060 2337	300 44	500 A A	/
	255/75R17	115T	6.5-7.0-8.5	6.5-7.0-8.5	7J	10.4	255	814	1215 2679	300 44	500 A A	/
	265/65R17	116T	7.5-8.0-9.5	7.5-8.0-9.5	8J	10.4	272	776	1250 2756	340 50	500 A A	/
	265/70R17	113T	7.0-8.0-9.0	7.0-8.0-9.0	8J	10.4	272	804	1150 2535	300 44	500 A A	/
	LT265/70R17	121/118S	/	7.0-8.0-9.0	8J	12.8	272	804	1450 3195	550 80	/	10PR/LRE
18"	LT285/70R17	121/118Q	/	7.5-8.5-9.5	8 1/2J	13.7	292	832	1450 3195	550 80	/	10PR/LRE
	NEW 225/55R18	102T	6.5-7-7.5	6.5-7-7.5	7	10	233	705	850 1874	340 49	500 A A	4PR
	NEW 225/60R18	104T	6-6.5-7	6-6.5-7	6.5	10	228	727	900 1984	340 49	500 A A	4PR
	NEW 265/60R18	114T	7.5-8-8.5	7.5-8-8.5	8	10	272	775	1180 2601	340 49	500 A A	4PR
	265/65R18	114H	7.5-8.0-9.5	7.5-8.0-9.5	8J	10.4	272	801	1180 2601	300 44	500 A A	/
	LT265/70R18	124/121_S	/	7.0-8.0-9.0	8J	12.8	272	829	1600 3527	550 80	/	10PR/LRE
	275/65R18	114T	7.5-8.0-9.5	7.5-8.0-9.5	8J	10.4	279	815	1180 2601	300 44	500 A A	/
	LT275/65R18	123/120_S	/	8.0-9.5	8J	11.5	279	815	1550 3417	550 80	/	10PR/LRE
	LT275/70R18	125/122S	/	7.0-8.0-9.0	8J	12.8	279	843	1650 3640	550 80	/	10PR/LRE
20"	NEW 285/60R18	116H	/	/	8.5	7.8	292	799	1400 3086	340 50	500AA	4PR
	NEW LT285/75R18	129/126Q	7.5-8-8.5	7.5-8-8.5	8	12.3	286	885	1850 4080	550 80	/	10PR
	NEW 265/50R20	111T	8-8.5-9	8-8.5-9	8.5	10	277	774	1090 2403	340 49	500 A A	4PR
	LT265/60R20	121/118_S	/	8.0-9.5	8J	12.8	272	826	1450 3197	550 80	/	10PR/LRE
	275/55R20	117H	7.5-8.5-9.5	7.5-8.5-9.5	8 1/2J	10.4	284	810	1285 2833	340 49	500 A A	/
	275/60R20	119H	7.5-8.0-9.5	7.5-8.0-9.5	8J	10.4	279	838	1360 2998	340 49	500 A A	/
22"	LT275/65R20	126/123S	/	8.0-9.5	8J	12.8	279	866	1700 3750	550 80	/	10PR/LRE
	LT285/55R20	122/119S	/	8.5-9.0-10.0	9J	12.5	297	822	1500 3305	550 80	/	10PR/LRE
	NEW 275/50R22	115T	8-8.5-9	8-8.5-9	8.5	10	284	835	1215 2679	340 49	500 A A	4PR
	285/45R22	116H	9.0-9.5-10.5	9.0-9.5-10.5	9 1/2J	10	285	815	1250 2756	340 49	500 A A	/

Tire sizes, technical data and product availability are subject to change. Please see arroyotires.com for the most up-to-date information.

SIZES
COMING
SOON

Wheel Dia.	TIRE SIZE
15"	255/70R15C
17"	LT315/70R17

Wheel Dia.	TIRE SIZE
18"	LT285/65R18

**ENJOY YOUR
JOURNEY**



TAMAROCK A/T

ARRROYO
TIRES



ARROYO
TIRES

SIDEWALL
3PLY

TAMAROCK M/T

Moderated Rubber to Void Ratio Reduces noise, Increases Wear character and Mileage. Attractive Marked Tread Design Produces great traction for all surface conditions. Aggressive & Profound Wrap Around Shoulder Elements are functional. 3 Polyester Body Plies for strength and resilience. 2 Wide Steel Belts Strengthen the overall tread area. Provides stability, excellent wear character & long mileage. Jointless Nylon Band Spiral wound for uniformity Increases strength in the high stress shoulder area.



AGGRESSIVE
TREAD DESIGN



LONGER
TREAD LIFE



STRONGER
SIDEWALL



QUIETER
RIDE



TAMAROCK M/T TIRES

ARROYOTIRES.COM



MUD-TERRAIN
Tamarock M/T Tires
TAMAROCK M/T



- SUV Metric Sizes - High Float
Sizes 17, 18, 20 & 22"
Rim Diameters
- 50, Series Aspect Ratios
& High Float
- 19/32 Tread Depth
- Moderated Rubber to Void Ratio
Reduces noise, Increases Wear
character and Mileage.
Attractive Marked Tread Design
Produces great traction for all
surface conditions.
Aggressive & Profound Wrap
Around Shoulder Elements
are functional.
- 3 Polyester Body Plies for strength
and resilience
- 2 Wide Steel Belts
Strengthen the overall tread area.
Provides stability, excellent wear
character & long mileage.
- Jointless Nylon Band
Spiral wound for uniformity
Increases strength in the high
stress shoulder area.



**SIZES
COMING
SOON**

Wheel Dia.	TIRE SIZE
15"	LT31x10.50R15
	33x12.50R15LT


Wheel Dia.	TIRE SIZE
15"	35X12.50R15LT
17"	LT285/70R17

TAMAROCK M/T

Wheel Dia.	TIRE SIZE	LOAD AND SPEED INDEX	EUROPEAN STANDARD RIM	AMERICAN STANDARD RIM	REC RIM WIDTH	TREAD DEPTH MM	SECTION WIDTH MM	OVERALL DIAMETER MM	MAX LOAD KGS LBS	MAX INFLATION KPA PSI	UTQG	PLY RATING
17"	33x12.50R17LT	120Q	/	8.5-10.0-11.0	10J	15.5	318	832	1400 3085	450 65	/	10PR/LRE
	35x12.50R17LT	125Q	/	8.0-10.0-10.5	10J	15.7	318	883	1650 3640	450 65	/	10PR/LRE
18"	33x12.50R18LT	122Q	/	8.5-10.0-11.0	10J	15.7	318	832	1500 3305	550 80	/	12PR/LRF
	35x12.50R18LT	128Q	/	8.5-10.0-11.0	10J	15.7	318	883	1800 3970	550 80	/	12PR/LRF
20"	33x12.50R20LT	119Q	/	8.5-10.0-11.0	10J	15.4	318	832	1360 3000	550 80	/	12PR/LRF
	35x12.50R20LT	125Q	/	8.5-10.0-11.0	10J	15.7	318	883	1650 3640	550 80	/	12PR/LRF
22"	33x12.50R22LT	114Q	/	8.5-10.0-11.0	10J	15.5	318	832	1180 2600	550 80	/	12PR/LRF
	35x12.50R22LT	121Q	/	8.5-10.0-11.0	10J	15.5	318	883	1450 3195	550 80	/	12PR/LRF

Tire sizes, technical data and product availability are subject to change. Please see arroyotires.com for the most up-to-date information.

PATTERN INTRODUCTIONS



- Excellent Driving Performance
The optimum ratio of rubber and void on the tread and the special stepped edge treatment removal of dirty under extreme off-road conditions effectively, ensuring the excellent driving performance.
- Water And Snow Drainage Performance
Wide and deep pattern groove design enhances the anti-skip performance of tires under rainy and snowy road greatly.



- Excellent Gripping Design
Solid square shoulder increases the contact area between tread and ground greatly, improves the grip and bearing capacity of wet and dry road, making more stable driving.
- Wearing And Stabbing Resistance
Aggressive sidewall design prevents damage and enhances grip when in deep mud or rock climbing.

ARROYO
TIRES



TAMAROCK
R/T

Super aggressive style with refined road manners. Large laterally oriented blocks provide extra biting grip with stepped- edge and bold sidewall elements. Lateral groove and zig-zag valleys create channels for water evacuation and snow traction. With a wide flat contact patch, the stable block design gives constant contact with the road ensuring smooth driving, aggressive grip in handling and outstanding all-weather performance on the road. Off-road, the many biting elements of the sidewalls, blocks and grooves will make short work of rocks, mud, sand or snow.



AGGRESSIVE
TREAD DESIGN




LONGER
TREAD LIFE



STRONGER
SIDEWALL



QUIETER
RIDE



RUGGED-TERRAIN
TAMAROCK R/T TIRES

ARROYOTIRES.COM



RUGGED-TERRAIN
Tamarock R/T Tires

TAMAROCK R/T



Super aggressive style with refined road manners. Large laterally oriented blocks provide extra biting grip with stepped- edge and bold sidewall elements. Lateral groove and zig-zag valleys create channels for water evacuation and snow traction. With a wide flat contact patch, the stable block design gives constant contact with the road ensuring smooth driving, aggressive grip in handling and outstanding all-weather performance on the road. Off-road, the many biting elements of the sidewalls, blocks and grooves will make short work of rocks, mud, sand or snow.



DUAL
SIDEWALL
FINISH
BLACK/RED

TAMAROCK R/T

Wheel Dia.	TIRE SIZE	LOAD AND SPEED INDEX	EUROPEAN STANDARD RIM	AMERICAN STANDARD RIM	REC RIM WIDTH IN.	TREAD DEPTH MM	SECTION WIDTH MM	OVERALL DIAMETER MM	MAX LOAD KGS LBS	MAX INFLATION KPA PSI	UTQG	PLY RATING
16"	NEW LT265/75R16	123/120Q	7-7.5-8	7-7.5-8	7.5	13.1	267	804	1550 3415	550 80	/	10PR
	NEW 265/65R17	116T	7.5-8-8.5	7.5-8-8.5	8	10	272	776	1250 2756	340 49	500 A A	4PR
	NEW LT265/70R17	123/120Q	7.5-8-8.5	7.5-8-8.5	8	13.1	272	804	1550 3415	550 80	/	10PR
	NEW 265/70R17	115T	7.5-8-8.5	7.5-8-8.5	8	10	272	804	1215 2679	300 44	500 A A	4PR
17"	NEW LT285/70R17	126/123Q	8-8.5-9	8-8.5-9	8.5	13.1	292	832	1700 3750	550 80	/	10PR
	NEW LT295/70R17	128/125Q	8-8.5-9	8-8.5-9	8.5	13.1	299	846	1800 3970	550 80	/	10PR
	NEW LT315/70R17	128/125Q	9-9.5-10	9-9.5-10	9.5	13.1	323	874	1700 3750	550 80	/	12PR
	NEW 33x12.50R17LT	124Q	9.5-10-10.5	9.5-10-10.5	10	13.1	318	826	1600 3525	550 95	/	12PR
	NEW 35x12.50R17LT	121Q	9.5-10-10.5	9.5-10-10.5	10	13.1	318	877	1450 3195	650 95	/	12PR
	NEW 37x12.50R17LT	128Q	9.5-10-10.5	9.5-10-10.5	10	13.1	318	928	1800 3970	450 65	/	12PR
18"	NEW 265/60R18	114T	7.5-8-8.5	7.5-8-8.5	8	10	272	775	1180 2601	340 49	500 A A	4PR
	NEW 265/65R18	116T	7.5-8-8.5	7.5-8-8.5	8	10	272	801	1250 2756	340 49	500 A A	4PR
	NEW LT265/70R18	124/121Q	7.5-8-8.5	7.5-8-8.5	8	13.1	272	829	1600 3525	550 80	/	10PR
	NEW 265/70R18	116T	7.5-8-8.5	7.5-8-8.5	8	10	272	829	1250 2756	300 44	500 A A	4PR
	NEW 275/65R18	116T	7.5-8-8.5	7.5-8-8.5	8	10	279	815	1250 2756	340 49	560 A A	4PR
	NEW LT275/65R18	123/120Q	7.5-8-8.5	7.5-8-8.5	8	13.1	279	815	1550 3415	550 80	/	10PR
	NEW LT275/70R18	128/125Q	7.5-8-8.5	7.5-8-8.5	8	13.1	279	843	1650 3640	550 80	/	12PR
	NEW LT285/65R18	125/122Q	8-8.5-9	8-8.5-9	8.5	13.1	292	827	1650 3640	550 80	/	10PR
	NEW LT285/75R18	129/126Q	7.5-8-8.5	7.5-8-8.5	8	13.1	286	885	1850 4080	550 80	/	10PR
	NEW LT295/70R18	129/126Q	8-8.5-9	8-8.5-9	8.5	13.1	299	871	1850 4080	550 80	/	10PR
	NEW 33x12.50R18LT	122Q	9.5-10-10.5	9.5-10-10.5	10	13.1	318	826	1500 3305	550 80	/	12PR
	NEW 35x12.50R18LT	128Q	9.5-10-10.5	9.5-10-10.5	10	13.1	318	877	1800 3970	550 80	/	12PR



DUAL
SIDEWALL
FINISH
BLACK/WHITE



RUGGED-TERRAIN
Tamarock R/T Tires

TAMAROCK R/T



TAMAROCK R/T

Wheel Dia.	TIRE SIZE	LOAD AND SPEED INDEX	EUROPEAN STANDARD RIM	AMERICAN STANDARD RIM	REC RIM WIDTH IN.	TREAD DEPTH MM	SECTION WIDTH MM	OVERALL DIAMETER MM	MAX LOAD KGS LBS	MAX INFLATION KPA PSI	UTQG	PLY RATING
20"	NEW 265/50R20	111T	8-8.5-9	8-8.5-9	8.5	10	277	774	1090 2403	340 49	500 A A	4PR
	275/55R20	117T	7.5-8.5-9.5	7.5-8.5-9.5	8 1/2J	10.5	284	810	1285 2833	340 50	500 A A	/
	NEW 275/60R20	116T	7.5-8-8.5	7.5-8-8.5	8	10	279	838	1250 2756	340 49	500 A A	4PR
	LT275/65R20		COMING SOON									
	NEW LT285/55R20	122/119Q	8.5-9-9.5	8.5-9-9.5	9	13.1	297	822	1500 3305	550 80	/	10PR
	NEW LT285/60R20	125/122Q	8-8.5-9	8-8.5-9	8.5	13.1	292	850	1650 3640	550 80	/	10PR
20"	NEW LT285/65R20	127/124Q	8-8.5-9	8-8.5-9	8.5	13.1	292	878	1750 3860	550 80	/	10PR
	NEW LT295/60R20	126/123Q	8-8.5-9	8-8.5-9	8.5	13.1	299	862	1700 3750	550 80	/	10PR
	NEW 305/55R20	116T	9-9.5-10	9-9.5-10	9.5	10	316	844	1250 2756	300 44	500 A A	4PR
	33x12.50R20LT	119Q 12PLY	/	8.5-10.0-11.0	10J	12.5	318	826	1360 3000	550 80	/	12PR/LRF
	NEW 35x12.50R20LT	125Q	9.5-10-10.5	9.5-10-10.5	10	13.1	318	877	1650 3640	550 80	/	12PR
	NEW 37x12.50R20LT	128Q	9.5-10-10.5	9.5-10-10.5	10	13.1	318	928	1700 3750	450 65	/	12PR
22"	NEW 275/50R22	115T	8-8.5-9	8-8.5-9	8.5	10	284	835	1215 2679	340 49	500 A A	4PR
	NEW 285/45R22	114H	9-9.5-10	9-9.5-10	9.5	10	285	815	1180 2601	340 49	500 A A	4PR
	NEW 305/45R22	118H	9.5-10-10.5	9.5-10-10.5	10	10	303	833	1320 2910	340 49	500 A A	4PR
	NEW 33x12.50R22LT	114Q	9.5-10-10.5	9.5-10-10.5	10	13.1	318	826	1180 2600	550 80	/	12PR
	NEW 35x12.50R22LT	121Q	9.5-10-10.5	9.5-10-10.5	10	13.1	318	877	1450 3195	550 80	/	12PR
	NEW 37x12.50R22LT	127Q	9.5-10-10.5	9.5-10-10.5	10	13.1	318	928	1750 3860	550 80	/	12PR
24"	33x12.50R24LT	106Q	11-11.5-12	11-11.5-12	11.5	13.1	320	826	825 1820	450 65	/	12PR
	35x12.50R24LT	116Q	10-10.5-11	10-10.5-11	10.5	13.1	316	877	1090 2405	450 65	/	12PR

Tire sizes, technical data and product availability are subject to change. Please see arroyotires.com for the most up-to-date information.


PATTERN INTRODUCTIONS




Lateral Grooves and Zigzag longitudinal design
Provide aggressive traction in rain, mud, snow and sand. Rock-crawler looks with impeccable on-highway manners



Concave and convex sidewall design
Concave and convex sidewall extend from the shoulder blocks down to the sidewall for extra off-road traction.



Stable block design
promotes even wear while providing a consistent contact patch and large outside tread elements for great dry handling



Stepped block edges, stepped block ties
Reduce irregular wear, fight stone retention and create additional biting surfaces for traction on wet surfaces, snow and Variable step shape block design for extra bite to get more traction.



TAMAROCK R/T



AGGRESSIVE
TREAD DESIGN



LONGER
TREAD LIFE



STRONGER
SIDEWALL



QUIETER
RIDE



DUAL SIDEWALL FINISH





RUGGED-TERRAIN
Tamarock XR/T Tires

TAMAROCK XR/T **NEW**



TAMAROCK XR/T

Wheel Dia.	TIRE SIZE
17"	33x12.50R17LT
	35x12.50R17LT
18"	33x12.50R18LT
	35x12.50R18LT
20"	33x12.50R20LT
	35x12.50R20LT
22"	33x12.50R22LT
	35x12.50R22LT

Super aggressive style with refined road manners. Large laterally oriented blocks provide extra biting grip with stepped- edge and bold sidewall elements. Lateral groove and zig-zag valleys create channels for water evacuation and snow traction. With a wide flat contact patch, the stable block design gives constant contact with the road ensuring smooth driving, aggressive grip in handling and outstanding all-weather performance on the road. Off-road, the many biting elements of the sidewalls, blocks and grooves will make short work of rocks, mud, sand or snow.



LONGER
TREAD LIFE



STRONGER
SIDEWALL



QUIETER
RIDE

**DUAL
SIDEWALL
FINISH**
BLACK/RED
BLACK/WHITE



TAMAROCK XR/T



NEW

ST
SPECIAL
TRAILER
SEMI-STEEL / ST

ST SEMI-STEEL

SEMI-STEEL / ST

Wheel Dia.	TIRE SIZE	LOAD AND SPEED INDEX	REC RIM WIDTH IN.	TREAD DEPTH MM	SECTION WIDTH MM	OVERALL DIAMETER MM	MAX LOAD KGS LBS	MAX INFLATION KPA PSI	UTQG	PLY RATING
13"	NEW ST175/80R13	97/93N	5.0JX13	7	177	610	730 1610	450 65	-	8PR
	NEW ST185/80R13	99/95N	5.0JX13	7	184	626	670 1480	350 50	-	8PR
	NEW ST185/80R13	-	-	-	-	-	- -	- -	-	6PR
14"	NEW ST205/75R14	100/96N	5.5JX14	7	203	664	800 1765	350 50	-	6PR
	NEW ST205/75R14	105/101N	5.5JX14	7	203	664	925 2040	450 65	-	8PR
	NEW ST215/75R14	108/103N	6.0JX14	7	216	678	1000 2200	450 65	-	8PR
15"	NEW ST205/75R15	101/97N	5.5JX15	7	203	689	825 1820	350 50	-	6PR
	NEW ST205/75R15	107/102N	5.5JX15	7	203	689	975 2150	450 65	-	8PR
	NEW ST205/75R15	111/106N	5.5JX15	7	203	689	1090 2400	550 80	-	10PR
	NEW ST225/75R15	113/108N	6.0JX15	7	223	719	1150 2540	450 65	-	8PR
	NEW ST225/75R15	117/112N	6.0JX15	7	223	719	1285 2830	550 80	-	10PR
	NEW ST235/85R16	125/121N	6.5JX16	7	235	806	1650 3640	550 80	-	10PR
16"	NEW ST235/85R16	128/124N	6.5JX16	7	235	806	1800 3960	660 95	-	12PR
	NEW ST235/80R16	124/120N	6.5JX16	7	235	782	1600 3520	550 80	-	10PR
	NEW ST235/80R16	127/122N	6.5JX16	7	235	782	1750 3860	690 100	-	12PR
	NEW ST225/90R16	129/125N	6.0JX16	7	223	810	1750 3860	660 95	-	12PR



NEW

ST
SPECIAL
TRAILER
ALL-STEEL / ST

ST ALL-STEEL

ALL-STEEL / ST

Wheel Dia.	TIRE SIZE	LOAD AND SPEED INDEX	REC RIM WIDTH IN.	TREAD DEPTH MM	SECTION WIDTH MM	OVERALL DIAMETER MM	MAX LOAD KGS LBS	MAX INFLATION KPA PSI	UTQG	PLY RATING
15"	NEW ST225/75R15	123/119N	6	8.3	223	719	1550 3420	760 110	-	14PR
16"	NEW ST225/90R16	129/125N	6	8.3	220	808	1850 4080	760 110	-	14PR
	NEW ST225/90R16	130/126L	6	8.3	220	808	1900 4190	760 110	-	16PR
	NEW ST235/80R16	129/125N	6.5	8.3	235	782	1850 4080	760 110	-	14PR
	NEW ST235/80R16	130/126L	6.5	8.3	235	782	1900 4190	760 110	-	16PR
	NEW ST235/85R16	132/127N	6.5	8.3	235	806	2000 4400	760 110	-	14PR
	NEW ST235/85R16	133/128L	6.5	8.3	235	806	2060 4540	760 110	-	16PR



AR1000 AR1100

SMART WAY

STEER / ALL-POSITION



AR2000 AR2200

SMART WAY

CLOSED-SHOULDER DRIVE



AR3000

REGIONAL

OPEN - SHOULDER DRIVE

AR4000

TRAILER

AR5000

REGIONAL

ON-OFF ROAD / MIXED-SERVICE

AR6000

REGIONAL

PICK-UP/DELIVERY / ALL-POSITION



AR SERIES
COMMERCIAL TBR

COMMERCIAL TRUCK TIRES

ARROYO
TIRES



AR 1000 AR1100 SMART WAY/ ALL-POSITION



SIZE	PLY	DEPTH (1/32")	LOAD INDEX	SPEED INDEX	O.D.	S.W.	R.W.	A.P.	MAX LOAD SINGLE	MAX LOAD DUAL
11R22.5	14/G	18/32	144/142	M	41.5	11.0	8.25	-	6175	5840
11R22.5	16/H	18/32	146/143	M	41.5	11.0	8.25	120	6610	6005
295/75R22.5	14/G	18/32	144/141	M	39.9	11.7	9.00	110	6175	5675
295/75R22.5	16/H	18/32	146/143	M	39.9	11.7	9.00	120	6610	6005
11R24.5	14/G	18/32	146/143	M	43.5	11.0	8.25	-	6610	6005
11R24.5	16/H	18/32	149/146	M	43.5	11.0	8.25	120	7160	6610
*285/75R24.5	14/G	18/32	144/141	M	41.3	11.1	8.25	-	6175	5675
*285/75R24.5	16/H	18/32	147/144	M	41.3	11.1	8.25	120	6780	6175
225/70R19.5	14/G	18/32	128/126	M	31.9	8.9	6.75	110	3970	3750
225/70R19.5	16/H	18/32	129/128	M	31.9	9.8	6.75	120	4190	3970
245/70R19.5	14/G	18/32	133/131	M	33.0	8.9	7.50	110	4540	4300
*245/70R19.5	16/H	18/32	135/133	M	33.0	9.8	7.50	120	4805	4540
*255/70R22.5	16/H	18/32	140/137	M	36.6	10.0	7.50	120	5510	5070

(*285/75R24.5) is ARS1100.

Tire sizes, technical data and product availability are subject to change. Please see americanroadstar.com for the most up-to-date information.



AR1000 AR1100
SMART WAY / ALL-POSITION



AR 1000- AR1100 - Premium Fuel-Efficient All-Position Specialized tread compound for low rolling resistance 5 Straight ribs with closed shoulders for constant contact and long wear Sipping, cross grooves and wavy channels at bottom of grooves improve wet traction.
220 Tread width



AR 1000 AR 1100



AR 2000 AR2200 SMART WAY/ CLOSED-SHOULDER DRIVE



SIZE	PLY	DEPTH (1/32")	LOAD INDEX	SPEED INDEX	O.D.	S.W.	R.W.	A.P.	MAX LOAD SINGLE	MAX LOAD DUAL
11R22.5	14/G	28/32	144/142	M	41.9	11.0	8.25	-	6175	5840
11R22.5	16/H	28/32	146/143	M	41.9	11.0	8.25	120	6610	6005
295/75R22.5	14/G	28/32	144/141	M	40.4	11.7	9.00	110	6175	5675
295/75R22.5	16/H	28/32	146/143	M	40.4	11.7	9.00	120	6610	6005
11R24.5	14/G	28/32	146/143	M	43.9	11.0	8.25	-	6610	6005
11R24.5	16/H	28/32	149/146	M	43.9	11.0	8.25	120	7160	6610
*285/75R24.5	14/G	28/32	144/141	M	41.8	11.1	8.25	-	6175	5675
*285/75R24.5	16/H	28/32	147/144	M	41.8	11.1	8.25	120	6780	6175

(*285/75R24.5) is AR2200.

Tire sizes, technical data and product availability are subject to change. Please see arroyotires.com for the most up-to-date information.



AR2000 AR2200
SMART WAY / CLOSED-SHOULDER DRIVE



AR 2000 - AR 2200 - Closed-Shoulder Drive-Position Specialized tread compound for low rolling resistance closed shoulders for constant contact and long wear Large blocks, sipping, cross grooves to improve wet traction Large inside lugs for improved traction in all conditions Stone ejectors in groove to reduce stone drilling Extra-deep 28/32 tread for maximum mileage.
220 Tread width



AR4000
TRAILER



The AR4000 trailer tire features a shallow tread, which is intended to reduce the rate of wear and prevent irregular wear. Though it is used on a non-dynamic axle, the casing construction of the AR4000 is the same as for tires on other wheel positions, which increases the casing’s value for retreading.

Serrated rib edges are incorporated into the design to reduce stress while multiple sipes contribute to excellent long-term wear characteristics. To assist with self-cleaning of the tread, serpentine graduated groove walls are incorporated into the design, helping the tire maintain grip in mud & dirt.

Overall, the shallow tread design of the AR4000 ensures that the tire performs well and lasts longer, providing reliable and cost-effective tire for trailer applications.

AR 4000 TRAILER

SIZE	PLY	DEPTH (1/32")	LOAD INDEX	SPEED INDEX	O.D.	S.W.	R.W.	A.P.	MAX LOAD SINGLE	MAX LOAD DUAL
11R22.5	16/H	13/32	148/145	M	41.5	11.0	8.25	123	6945	6395
295/75R22.5	14/G	13/32	144/141	M	39.9	11.7	9.00	110	6175	5675
11R24.5	14/G	13/32	146/143	M	43.5	11.0	8.25	105	6610	6005
285/75R24.5	14/G	13/32	144/141	M	41.3	11.1	8.25	110	6175	5675

Tire sizes, technical data and product availability are subject to change. Please see arroyotires.com for the most up-to-date information.



AR4000

TRAILER



The AR4000 trailer tire features a shallow tread, which is intended to reduce the rate of wear and prevent irregular wear. Though it is used on a non-dynamic axle, the casing construction of the AR4000 is the same as for tires on other wheel positions, which increases the casing’s value for retreading.

Serrated rib edges are incorporated into the design to reduce stress while multiple sipes contribute to excellent long-term wear characteristics. To assist with self-cleaning of the tread, serpentine graduated groove walls are incorporated into the design, helping the tire maintain grip in mud & dirt.

Overall, the shallow tread design of the AR4000 ensures that the tire performs well and lasts longer, providing reliable and cost-effective tire for trailer applications.

AR 4000 TRAILER

SIZE	PLY	DEPTH (1/32")	LOAD INDEX	SPEED INDEX	O.D.	S.W.	R.W.	A.P.	MAX LOAD SINGLE	MAX LOAD DUAL
11R22.5	16/H	13/32	148/145	M	41.5	11.0	8.25	123	6945	6395
295/75R22.5	14/G	13/32	144/141	M	39.9	11.7	9.00	110	6175	5675
11R24.5	14/G	13/32	146/143	M	43.5	11.0	8.25	105	6610	6005
285/75R24.5	14/G	13/32	144/141	M	41.3	11.1	8.25	110	6175	5675

Tire sizes, technical data and product availability are subject to change. Please see arroyotires.com for the most up-to-date information.



AR5000

ON-OFF / MIXED-SERVICE ALL-POSITION

The all-position mixed-service tread design of the AR5000 is robust and suitable for many on/off-highway applications. The tire features three large zig-zag circumferential grooves that provide excellent traction in a variety of surface conditions. An indented outside shoulder rib, coupled with zig-zag interior ribs, create grabbing surfaces in mud, rock, and sand.

The tire's resilient tread compound promotes long wear even in harsh conditions, making it ideal for rugged mixed-service applications.



AR 5000 ON-OFF / MIXED-SERVICE ALL-POSITION

SIZE	PLY	DEPTH (1/32")	LOAD INDEX	SPEED INDEX	O.D.	S.W.	R.W.	A.P.	MAX LOAD SINGLE	MAX LOAD DUAL
11R22.5	16/H	21/32	146/143	N	41.5	11.0	8.25	120	6610	6005
275/70R22.5	18/J	18/32	148/145	N	37.7	10.9	8.25	131	6940	6395
315/80R22.5	20/L	20/32	157/154	N	42.4	12.3	9.00	130	9090	8270
385/65R22.5	20/L	19/32	160	M	42.2	15.3	11.75	130	9920	-
425/65R22.5	20/L	21/32	165	N	44.3	16.6	12.25	120	11400	-
11R24.5	16/H	21/32	149/146	N	43.5	11.0	8.25	120	7160	6610

Tire sizes, technical data and product availability are subject to change. Please see arroyotires.com for the most up-to-date information.

AR 5000



AR6000
REGIONAL /ALL-POSITION

The all-position AR6000 all-steel radial tire is designed specifically for pick-up/delivery applications, with solid outside ribs that offer strength and resilience to curbing. The undulating circumferential grooves are designed to provide excellent water evacuation, ensuring grip in wet conditions. Additional siping on the interior ribs provides extra biting edges for traction in various surface conditions while serrated center ribs increase traction and reduce irregular wear.



AR 6000 REGIONAL / ALL-POSITION

SIZE	PLY	DEPTH (1/32")	LOAD INDEX	SPEED INDEX	O.D.	S.W.	R.W.	A.P.	MAX LOAD SINGLE	MAX LOAD DUAL
215/75R17.5	16/H	16/32	135/133	L	30.2	8.3	6.00	123	4805	4540
235/75R17.5	18/J	16/32	143/141	L	31.4	9.2	6.75	127	6005	5675
245/70R17.5	18/J	16/32	143/141	K	31.1	9.8	7.5	130	6005	5675

Tire sizes, technical data and product availability are subject to change. Please see arroyotires.com for the most up-to-date information.

AR 6000



ARROYO PASSENGER / LIGHT TRUCK TIRE
LIMITED WARRANTY

*This warranty applies only to tires purchased in the United State
on or after October 01, 2018*

This Limited Warranty is made by WTD (Wholesale Tire Distributor) & applies to the Arroyo passenger & light truck tires listed on the summary of Limited Warranty Coverage Chart. The original purchaser is entitled to the benefits of this limited warranty unless a warranty exclusion applies or the purchaser has failed to comply with this Limited Warranty's use, maintenance, or tire rotation requirements. This warranty applies only to tires purchased on or after October 01,2018

"A. Eligibility for Limited Warranty Coverage

You must be the original purchaser on or after October 01,2018 of a warranted tire & the tire must have been continuously installed on the vehicle on which it was first installed. Your sales receipt is your proof of purchase & the vehicle upon which the tire was originally installed. This limited tire warranty is not transferable to another vehicle or to another person. This warranty does not cover tires installed on a commercial vehicle or a vehicle put in commercial use. To be & remain eligible for the Tread Life portion of your Limited Warranty, you must present proof that you have rotated the Arroyo tire, in accordance with the prescribed rotation pattern, at least every 3,000 - 4,000 miles following installation.

"B. Materials and Workmanship Warranty

Selected Arroyo tread patterns (indicated in the warranty chart of this document) are warranted against defects in materials and workmanship and will be replaced free of charge within the first 2/32" wear of original usable tread life, or within 6 months from the period of purchase, whichever comes first. After the 100% replacement term expires and the tire is still within 60 months from the manufacturing date, credit will be determined by the percentage of original tread depth remaining on the tire. Any additional costs of mounting, balancing, installation charges, shipping, and any applicable sales tax or use taxes are not covered."

"C. Limited Mileage Warranty

Selected Arroyo tread patterns (indicated in this document) are manufactured to protect against premature tread wear. If a tire reaches the end of its usable tread life (2/32") before the stated mileage warranty (indicated in this document) the original purchaser will be issued a comparable Arroyo Tire on a pro-rata basis, based on the percentage of remaining usable tread depth down to the remaining 2/32" tread depth. Tread must be worn down evenly across the face of the tread. In order to maintain this limited warranty, all tires must be rotated at least every 3,000-4,000 miles. Any additional costs of mounting, balancing, installation charges, shipping, and any applicable sales tax or use taxes are not covered. Documentation is required showing alignment, tire rotation records, along with date of installation and removal to maintain tread wear warranty. Tires MUST be rotated 3,000-4,000 miles. Tread must be worn down evenly across the face of the tread."

"D. Exclusions Not Covered Under This Limited Warranty

- Tires used on RVs (recreational vehicles), Motor Homes, Trailers, or tires used in commercial service.
- Tires that are used in a staggered application where tires on the back of the vehicle are a different size than those on the front.
- Any tire that has any brand information, sizes, or the D.O.T. identification numbers removed intentionally
- Ride complaints after the first 2/32" of tread wear or replacement of 3 or more tires from the same vehicle will not be accepted..

- Premature/irregular wear due to vehicle mechanical deficiencies.
- Failure to rotate the tires at recommended intervals.
- Road hazard damage including cuts, snags, bruises, punctures,tire repair, impact breaks, etc. (Select tires indicated in this document have coverage under the Arroyo Tire Road Hazard Policy.)
- Any tires on any vehicle that are registered and normally operated outside the U.S.
- Any damage from over/under inflation, tire overloading, fire, theft, and any defective mechanical condition of the vehicle.
- Any damage from incorrect tire mounting/dismounting/ balancing, any incorrect tire application, water orany other material trapped inside the tire during tire mounting.
- Any racing or other misapplication of tire to improper road conditions.
- Environmental ozone or weather cracking after 48 months from tire manufacture date.
- Any accident, fire, chemical corrosion, tire alteration, vandalism, abuse, or running on a flat tire.
- Any tires worn beyond the tire bar wear indicators and less than 2/32".
- Uneven wear in which the tread groove difference is 2/32" or more across the face of the tire.
- Any loss of time or use, inconvenience, any incidental or consequential damage.
- Flat spotting caused by improper storage or brake lock."

"F. Road Hazard Warranty

Arroyo Brand Tires sold in the US by authorized Arroyo Tire dealers, are assigned a Road Hazard Warranty that protects the consumer against non-repairable damage caused by puncture, snag, cut, bruise or impact break. Typical road hazards are nails, glass, potholes and other debris. If road hazard damage occurs within first 25% wear of the tire's usable tread or the first 6 months, whichever coms first, a replacement will be made with a comparable Arroyo tire 100% free of charge. If the damage occurs before 50% of the tread has been warn away or within the first 12 months of purchase, whichever comes first, the Arroyo Tire Dealer will reimburse 50% of the original cost.

Under all circumstances, the cost of mounting, balancing and any other service charges including applicable taxes are required to be paid by the consumer.

What is not covered under the Road Hazard Replacement Program?

- A tire that has failed or damaged due to an accident.
- A tire that has failed or damaged due to vandalism.
- A tire that has repairable damage under Rubber Manufacturers Association (RMA) standards.
- A tire that has failed or damaged due to commercial use.
- A tire that has failed or damaged due to racing or off-road use.
- A tire that has failed or damaged due to the use of snow chains or studs.
- A tire that has failed or damaged due to irregular wear caused by mechanical issues.
- Tires transferred from the vehicle that they were originally installed on.
- A tire that is past 2 years from the date of purchase or first 50% of tread wear, whichever comes 1st.- Run-flat tires are not in the scope of this warranty."

LIMITED TIRE WARRANTY REGISTRATION NUMBER
(To be completed at the time of purchase:)

Date: _____ Odometer: _____
Customer Information:
Name: _____
Address: _____
City: _____ State: _____
Phone No.: _____

Vehicle Information:
Year: _____ Make/Model: _____
Tire Brand Purchased: _____
Tire Size/Pattern: _____
Recommended Tire Pressure Front: _____ PSI _____
Recommended Tire Pressure Rear: _____ PSI _____

DOT No. Information:
Tire #1 _____
Tire #2 _____
Tire #3 _____
Tire #4 _____

Tire Removal Information:
Date: _____ Odometer: _____
Dealer Name: _____
Dealer Address: _____
Dealer Signature: _____

IMPORTANT Tire Owner – Keep this page as part of your limited warranty claim. (invoice) must be submitted to an authorized Arroyo Tire Dealer
1. The information on this page must be completed to validate any limited warranty claim.
2. In the event of a limited warranty claim, this information and proof of purchase (copy of invoice) must be submitted to an authorized Arroyo Tire Dealer.

MILEAGE WARRANTY ADJUSTMENT TABLE							
Percent WTD pays per original warranty mileage on Arroyo Tires*							
Mileage up to	30,000	40,000	50,000	Mileage up to	30,000	40,000	50,000
1000	97%	98%	98%	26000	13%	35%	48%
2000	93%	95%	96%	27000	10%	33%	46%
3000	90%	93%	94%	28000	7%	30%	44%
4000	87%	90%	92%	29000	3%	28%	42%
5000	83%	88%	90%	30000	0%	25%	40%
6000	80%	85%	88%	31000		23%	38%
7000	77%	83%	86%	32000		20%	36%
8000	73%	80%	84%	33000		18%	34%
9000	70%	78%	82%	34000		15%	32%
10000	67%	75%	80%	35000		13%	30%
11000	63%	73%	78%	36000		10%	28%
12000	60%	70%	76%	37000		8%	26%
13000	57%	68%	74%	38000		5%	24%
14000	53%	65%	72%	39000		3%	22%
15000	50%	63%	70%	40000		0%	20%
16000	47%	60%	68%	41000			18%
17000	43%	58%	66%	42000			16%
18000	40%	55%	64%	43000			14%
19000	37%	53%	62%	44000			12%
20000	33%	50%	60%	45000			10%
21000	30%	48%	58%	46000			8%
22000	27%	45%	56%	47000			6%
23000	23%	43%	54%	48000			4%
24000	20%	40%	52%	49000			2%
25000	17%	38%	50%	50000			0%



ARROYO COMMERCIAL TIRE LIMITED WARRANTY

This warranty applies only to tires purchased in the United State on or after October 01, 2018

This Limited Warranty Policy provides for tire replacement under certain specified conditions. This policy applies to all ARROYO Radial Truck tires used in normal highway service displaying warrant able conditions. There is no warranty for tires that wear out, fail or become unserviceable because of neglect or mistreatment. It is essential that you adhere to all standard safety and maintenance practices and that you carefully read the terms and conditions defined in this Warranty. Wholesale Tire Distributors hereby warrants that every new ARROYO Radial Truck tire is free from defects in workmanship and material for the life of the original tread of the new tire less 2/32". The life of the original usable tread ends when the tire has worn down with only 2/32" remaining. Once the tread is worn down to the top of the built-in "wear indicators" in the tread grooves molded at 2/32", the tire is considered fully worn out regardless of its age or mileage. This warranty applies to ARROYO Radial Truck tires purchased through an authorized dealer of Wholesale Tire Distributors (WTD).

RECOMMENDED SAFETY PRACTICES

Serious injury or property damage may result from:

- TIRE FAILURE DUE TO UNDERINFLATION, OVERINFLATION and/or OVERLOADING
- Not following the owner's manual or tire placard in vehicle
- TIRE FAILURE DUE TO EXCESSIVE HIGH SPEED. Follow the owner's manual or tire placard in vehicle.
- EXPLOSION OF TIRE /RIM ASSEMBLY DUE TO IMPROPER MOUNTING. Only specially trained people should mount tires.
- FAILURE TO MOUNT RADIAL TIRES ON APPROVED RIMS.
- FAILURE TO DEFLATE SINGLE OR DUAL ASSEMBLIES COMPLETELY BEFORE DISMOUNTING.
- TIRE SPINNING. On slippery surfaces such as rain, snow, mud, ice etc. do not spin tires as personal injury and severe damage may result from excessive wheel spinning, including tire disintegration or axle damage.

WARRANTY ELIGIBILITY

This policy applies to the original equipment and aftermarket consumer/owner, or user of any new ARROYO radial truck tire sold through an authorized dealer of Wholesale Tire Distributors. Eligible tires must bear the ARROYO brand name, a complete D.O.T. serial identification number, NOT be branded as Non-Adjustable (NA) and operated in normal highway service. Eligible tires must be on the vehicle on which they were originally installed, in conformance with the vehicle manufacturer's recommendations. These tires are covered by this warranty for the life of the original usable tread depth (the original tread depth down to the level of treadwear indicators molded at 2/32 inch) within 72 months from the date of purchase (proof of purchase required). If proof of purchase is not available, the coverage will be 72 months from the date of manufacture.

50% FREE REPLACEMENT

If a defect in workmanship and materials is found in any ARROYO Radial Truck tire within the first 50% of the original usable tread (original tread depth, less 2/32", divided by 2), Wholesale Tire Distributors will replace such tire with a comparable new tire. Mounting and balancing services up to \$16.00/tire are covered in the form of a credit on the replacement tire invoice. Other applicable taxes and fees for the comparable new ARROYO tire are payable by the owner.

50% FREE REPLACEMENT WARRANTY

If a defect in workmanship and materials is found in any ARROYO Radial Truck tire after the first 50% of the original usable tread, a credit will be given toward the purchase of a comparable new ARROYO tire; pro-rated based on the usable tread depth remaining on the returned tire versus the original tread of the new tire. Applicable taxes and amount equal to the full current Federal Excise Tax (FET) on the new tire and costs of mounting and balancing services will be borne by the owner. Adjustments on out-of-balance or out-of-round tires are allowed only during the first 2/32" or 10% of the original tread.

EXCLUSIONS

- A. All ARROYO warranties are limited to the original purchaser and the original vehicle on which they are mounted. Warranties are not assignable to subsequent purchasers or vehicles.
- B. This limited warranty is valid only in the United States. Any tire used or equipped on a vehicle registered or regularly operated outside the United States is not covered by this warranty.
- C. The following is not covered by the Limited Warranty:
- a. Tire branded or marked "Non-Adjustable" (N/A) or "Blemished" (Blem), or previously adjusted.
 - b. Failure, damage or irregular wear due to:
 - Road hazards (i.e., puncture, cut, snag, impact breaks, etc.), wreck or collision.
 - Fire, accident or vandalism.
 - Mechanical condition of vehicle, including misalignment, wheel imbalance, faulty shocks or brakes.
 - Misapplication of tire, use of improper inner tube.
 - Alteration of the tire or addition of alien material or transfer from one vehicle to another.
 - Faulty retreading or repairing procedures or materials used in the retreading process.
 - c. Cost of mounting and balancing services except as noted.
 - d. Loss of time or use, inconvenience, or any incidental or consequential damages.
 - e. Tires operated at speeds that exceed posted limits, and tires used in racing or competition.
 - f. Tires used in non-standard applications.
 - g. Tires designed for highway use operated in off-road conditions.
 - h. Tires that are improperly repaired including, but not limited to; sidewall modification by addition or removal of material, tubeless tires into which anything other than air has been introduced including foam, dry or liquid balancers and sealants.
 - i. Tire/tube failure and air loss that has resulted from tube manufacturing deficiencies, tube deterioration, tire under/over inflation, improper tube and flap assembly, mounting tool damage, use of wrong size tube or a used tube, a bias tube in a radial application, applying an incompatible mounting lubricant, foreign objects contacting tube assembly.
 - j. Wholesale Tire Distributors does not warrant tubes, tube fitment, tube usage or the consequences thereof unless supplied by Wholesale Tire Distributor with the tire as a set.
 - k. Tires subjected to vehicle suspension deficiencies, wheels misalignment, improperly maintained balance of inflation
 - l. Tires submitted for ride disturbance complaints after the first two thirty-seconds of an inch (2/32") new tread wear.
 - m. Tires with the Department of Transportation (DOT) number removed.
 - n. Tires worn past the last two thirty-seconds of an inch (2/32") of original tread depth.
 - o. Ozone cracking or weather checking on tires submitted more than four years (4) after the date of manufacture.
 - a. Tires rendered not retreadable or unserviceable due to faulty or improper retreading. Improper retreading includes buffing to the cord surface, insufficient vulcanization, improper repair and failure of the bonding agent.
 - b. Wholesale Tire Distributor Tire does not warrant inspection for retread ability, the retread process, design, workmanship or materials.

CASING POLICY

- a. Casings of ARROYO radial truck tires are warranted against defects in workmanship and material throughout the original life, first retread, and second retread, (see c. below for restrictions). Defects in workmanship or materials found in the process of buffing for retread are warrantable. The number of retreads must be clearly identified on the casing sidewall.
- b. If an examination shows that a casing of an ARROYO radial truck tire failed due to a defect in workmanship or material, Wholesale Tire Distributors will give a credit towards the purchase price of a comparable new ARROYO tire based on the values listed below:

SIZE	CASING VALUE (US\$)	SIZE	CASING VALUE (US\$)
215/75R17.5	\$20	295/75R22.5	\$65
235/75R17.5	\$20	11R24.5	\$65
255/70R22.5	\$55	285/75R24.5	\$65
275/70R22.5	\$55	12R22.5	\$65
225/70R19.5	\$25	315/80R22.5	\$65
245/70R19.5	\$25	385/65R22.5	\$75
10R22.5	\$45	425/65R22.5	\$80
11R22.5	\$65	445/50R22.5	\$80

- c. Above casing warranty valid only for first six (6) years after date of manufacture of original tire for all casings. Casing value is reduced by 50% of the above values for the second retread.

OWNERS' OBLIGATIONS

- In order to be eligible for ARROYO Limited Warranty service, the owner must:
- Present the defective tire to an authorized ARROYO dealer.
 - Present proof of purchase to the satisfaction of the dealer.
 - Pay the amount due on a new tire, less the amount of credit, including taxes, mounting and balancing charges (except as noted) or cost of other services ordered.
 - Ensure proper tire maintenance, inflation pressures & loading practices in accordance with vehicle and applicable tire guides, as well as lawful operation of vehicles and adherence to government regulations. Wholesale Tire Distributors offers a guide to maintenance and care of ARROYO tires in the form of a section entitled, "Safety Practices" (above). It is strongly recommended that these guidelines be read.

LEGAL RIGHTS

To the extent permitted by law, Wholesale Tire Distributors and its servicing agents shall not be held responsible for any of the following:

- Commercial Loss.
- Damage to or loss of property other than the tire itself.
- Incidental, indirect, special or consequential damages arising from any cause whatsoever, including negligence.

Some states do not allow the exclusion or limitation. of incidental or consequential damages, so the above limitation or exclusions may not apply to you. No representative or dealer has authority to make any representation, promise, or agreement on behalf of Wholesale Tire Distributors except as stated herein. Any tire, no matter how well constructed, may fail in service or otherwise become unserviceable due to conditions beyond the control of the manufacturer. Under no circumstances is this representation that a tire failure cannot occur. This warranty gives you specific legal rights, and you may also have other rights that vary from state to state. This limited warranty is applicable only in the United States. No implied or express warranties are extended beyond the time when the tire has delivered its original tread life, except for the express warranties set forth in this "Limited Warranty". All warranties, promises and agreements, express or implied, merchantability or otherwise, are excluded to the extent permitted by law.

DISCLAIMER

This warranty, or any warranty stored or referenced to herein, is exclusive and in lieu of any other warranty regarding the quality of ARROYO tires whether expressed or implied, and remedies for breach thereof shall be limited to those specifically provided herein.



AR SERIES COMMERCIAL TBR



PERFORMANCE
SERIES

TAMAROCK
SERIES



SUMMARY OF LIMITED TIRE WARRANTY COVERAGE BY ARROYO TREAD PATTERN

Pattern / Product Name	Tread Wear/Mileage Warranty	Road Hazard Replacement Warranty	First Year / First 2/32nds	Second Year & Within the First 50% of Tread Depth
Eco Pro A/S - All Rim Diameters	50,000 Miles	Yes	Free	Prorated
Grand Sport A/S - 15,16 & 17" Rim Diameters	50,000 Miles	Yes	Free	Prorated
Grand Sport A/S - 18,19,20,22 & 24" Rim Diameters	40,000 Miles	Yes	Free	Prorated
Grand Sport 2 - 13,14,15,16&17" Rim Diameters	50,000 Miles	Yes	Free	Prorated
Grand Sport 2 - 18,19 & 20" Rim Diameters	40,000 Miles	Yes	Free	Prorated
Ultra-Sport A/S - All Rim Diameters	40,000 Miles	Yes	Free	Prorated
Eco Pro H/T - SUV & CSUV only	50,000 Miles	Yes	Free	Prorated
Eco Pro H/T2	55,000 Miles	Yes	Free	Prorated
Van Pro 2	N/A	N/A	N/A	N/A
All Terrain	50,000 Miles	Yes	Free	Prorated
Mud Terrain	N/A	N/A	N/A	N/A

** LT Metric Sizes is not included in this Limited Mileage and Road Hazard Warranty.

** Eligible tires for this warranty must meet the vehicle specifications of the original size applied at Original Equipment

NOTE: In the event of a warranty claim, this page must be attached to the Arroyo standard claim form.

ARROYO TIRES BF.1



WWW.ARROYOTIRES.COM



@arroyotires